



7701GT

7701G SERIES • GAS BALL VALVE • ONE-PIECE BODY FORGED BRASS

Item No.	Size	Connection	Inner Qty.	Master Qty.	Each Wt.
----------	------	------------	------------	-------------	----------

STYLE 7701GT – TEE HANDLE

111-523	1/2"	FPT x FPT	10	100	0.39
111-524	3/4"	FPT x FPT	10	100	0.57
111-525	1"	FPT x FPT	6	30	1.05

- 200 PSI
- -20°F - 300°F temperature range
- T-handle provides easy-to-turn operation
- Coated aluminum handle for corrosion and solvent resistance
- Multi-directional flow
- One-piece body for leak resistance and long valve life

- Chrome-plated brass ball
- CSA - ANSI Z21.15 (1/2 PSIG)
- ANSI/ASME B16.44 (5G)
- UL listed
- Threaded ends comply with ANSI B1.20.1



7701GFH

7701G SERIES • GAS BALL VALVE • ONE-PIECE BODY FORGED BRASS

Item No.	Size	Connection	Inner Qty.	Master Qty.	Each Wt.
----------	------	------------	------------	-------------	----------

STYLE 7701GFH – FLAT/SQUARE HEAD

113-523	1/2"	FPT x FPT	10	100	0.37
113-524	3/4"	FPT x FPT	10	100	0.55
113-525	1"	FPT x FPT	6	36	1.00
113-526	1-1/4"	FPT x FPT	4	24	1.44

- 200 PSI
- -20°F - 300°F temperature range
- Flat head operation prevents unintentional operation valve
- Coated aluminum handle for corrosion and solvent resistance
- Multi-directional flow
- One-piece body for leak resistance and long valve life

- Chrome-plated brass ball
- CSA - ANSI Z21.15 (1/2 PSIG)
- ANSI/ASME B16.44 (5G)
- UL listed
- Threaded ends comply with ANSI B1.20.1



7701GST

7701G SERIES • GAS BALL VALVE • ONE-PIECE BODY • SIDE TAPPED FORGED BRASS

Item No.	Size	Connection	Inner Qty.	Master Qty.	Each Wt.
----------	------	------------	------------	-------------	----------

STYLE 7701GST – FEMALE X FEMALE

110-553	1/2"	FPT x FPT	10	100	0.42
110-554	3/4"	FPT x FPT	10	100	0.61
110-555	1"	FPT x FPT	6	30	1.12

- 200 PSI
- -20°F - 300°F temperature range
- T-handle provides easy-to-turn operation
- Coated aluminum handle for corrosion and solvent resistance
- Multi-directional flow
- One-piece body for leak resistance and long valve life
- Chrome-plated brass ball

- 1/8" NPT side tap for pressure test, drain, line extension, and more (plug included)
- Save on parts & labor by attaching manometer to line testing at valve
- CSA - ANSI Z21.15 (1/2 PSIG)
- ANSI/ASME B16.44 (5G)
- UL listed
- Threaded ends comply with ANSI B1.20.1

