



RESIDENTIAL/COMMERCIAL Twin Stage Regulators

Type 988TW Compact



988TW-17

Type 998TW



988TW-11

Product description

The twin stage regulator consists of two regulation levels, which regulates the inlet pressure, coming from the container directly to the inlet pressure of the user appliance.

Type 988 TW Compact regulators are designed for Type B installations, found in the installation section. They are to be used outdoors in correct mounting position with vent-hole turned downwards. In the standard version, Type 988 TW regulators are delivered with vent-hole turned in line with to the outlet fitting.

Technical Specifications

Body And Cover: Aluminium

Diaphragm: Reinforced

Supplying Pressure: 25-250 PSIG

Cover Screws: Stainless Steel

Inlet Fitting Screws: Stainless Steel

Gas Type: Propane

Setting Point: inlet Pressure 10 PSIG, 140,000 BTU, Outlet Pressure 11" w.c.

Provided Flows: Flow Based On 10 PSIG Inlet Pressure with a 20% Drop (In accordance with UL 144)

Type 988TW - L 6.692 x W 4.33 x H 4.94" Weight: 39.75 oz

Type 998TW - L 7.055 x W 5.657 x H 4.964" Weight: 54.875 oz

Type (Part No.)	Capacities in BTU/ hr propane	Inlet connection, inches	Outlet connection, inches	Outlet pressure range, inches w.c.	Outlet pressure setting, inches w.c.
988TW - 15 (98.1.890.0015)	750,000	1/4" NPT	1/2" NPT	9 to 13	11
988TW - 16 ¹ (98.1.890.0016)					
988TW - 18 ¹ (98.1.890.0018)		POL	3/4" NPT		
988TW - 17 (98.1.890.0017)					
988TW - 28 (98.1.890.0028)					
998TW - 11 (99.1.890.0011)	1,400,000	1/4" NPT	3/4" NPT	9 to 13	11
998TW - 12 ¹ (99.1.890.0012)					
998TW - 13 (99.1.890.0013)		POL	1/2" NPT		
998TW - 14 ¹ (99.1.890.0014)					
998TW - 20 (99.1.890.0020)	750,000	1/4" NPT	1/2" NPT		
998TW - 21 (99.1.890.0021)		POL			

¹ First and Second-Stage spring case vents opposite gauge taps