# **SAFETY DATA SHEET**



#### Halocarbon R-416A

### **Section 1. Identification**

**GHS** product identifier

: Halocarbon R-416A

Other means of identification

: FR-12; FRIGC®; ASPEN R416A

**Product type** 

: Gas.

Product use Synonym

: Synthetic/Analytical chemistry.: FR-12; FRIGC®; ASPEN R416A

SDS#

: 006058

Supplier's details

: Airgas USA, LLC and its affiliates 259 North Radnor-Chester Road

Suite 100

Radnor, PA 19087-5283

1-610-687-5253

24-hour telephone

: 1-866-734-3438

### Section 2. Hazards identification

**OSHA/HCS** status

: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture

: GASES UNDER PRESSURE - Compressed gas HAZARDOUS TO THE OZONE LAYER - Category 1

#### **GHS** label elements

**Hazard pictograms** 





Signal word

: Warning

**Hazard statements** 

: Contains gas under pressure; may explode if heated.

Harms public health and the environment by destroying ozone in the upper atmosphere.

May displace oxygen and cause rapid suffocation.

#### **Precautionary statements**

**General** 

: Read and follow all Safety Data Sheets (SDS'S) before use. Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand. Close valve after each use and when empty. Use equipment rated for cylinder pressure. Do not open valve until connected to equipment prepared for use. Use a back flow preventative device in the piping. Use only equipment of compatible materials of construction.

Prevention: Not applicable.Response: Not applicable.Storage: Protect from sum

Storage : Protect from sunlight. Store in a well-ventilated place.

Hazards not otherwise

classified

**Disposal** 

Refer to manufacturer or supplier for information on recovery or recycling.In addition to any other important health or physical hazards, this product may displace

oxygen and cause rapid suffocation.

Date of issue/Date of revision : 9/16/2021 Date of previous issue : 12/9/2017 Version : 1.01 1/11

Halocarbon R-416A

# Section 3. Composition/information on ingredients

Substance/mixture

Other means of : FR-12; FRIGC®; ASPEN R416A

: Mixture

identification

Product code : 006058

Ingredient name	%	CAS number
	59 39.5 1.5	811-97-2 2837-89-0 106-97-8

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

#### Section 4. First aid measures

#### **Description of necessary first aid measures**

**Eye contact**: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower

eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10

minutes. Get medical attention if irritation occurs.

**Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If

not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects

persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar,

tie, belt or waistband.

**Skin contact**: Flush contaminated skin with plenty of water. Remove contaminated clothing and

shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean

shoes thoroughly before reuse.

**Ingestion**: As this product is a gas, refer to the inhalation section.

#### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

**Eye contact**: Contact with rapidly expanding gas may cause burns or frostbite.

**Inhalation** : No known significant effects or critical hazards.

Skin contactContact with rapidly expanding gas may cause burns or frostbite.FrostbiteTry to warm up the frozen tissues and seek medical attention.

**Ingestion**: As this product is a gas, refer to the inhalation section.

#### **Over-exposure signs/symptoms**

Eye contact : No specific data.
Inhalation : No specific data.
Skin contact : No specific data.
Ingestion : No specific data.

#### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

**Specific treatments**: No specific treatment.

**Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may

be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

Date of issue/Date of revision : 9/16/2021 Date of previous issue : 12/9/2017 Version : 1.01 2/11

### Section 4. First aid measures

See toxicological information (Section 11)

### Section 5. Fire-fighting measures

#### **Extinguishing media**

Suitable extinguishing media

: Use an extinguishing agent suitable for the surrounding fire.

**Unsuitable extinguishing** media

: None known.

#### Specific hazards arising from the chemical

**Hazardous thermal** decomposition products : Contains gas under pressure. In a fire or if heated, a pressure increase will occur and the container may burst or explode.

: Decomposition products may include the following materials: carbon dioxide carbon monoxide

halogenated compounds

#### **Special protective actions** for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Contact supplier immediately for specialist advice. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

#### **Special protective** equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

#### Section 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Avoid breathing gas. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For nonemergency personnel".

#### **Environmental precautions**

Ensure emergency procedures to deal with accidental gas releases are in place to avoid contamination of the environment. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). May be harmful to the environment if released in large quantities.

#### Methods and materials for containment and cleaning up

**Small spill** Large spill

- : Immediately contact emergency personnel. Stop leak if without risk.
- : Immediately contact emergency personnel. Stop leak if without risk. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

# Section 7. Handling and storage

#### **Precautions for safe handling**

**Protective measures** 

: Put on appropriate personal protective equipment (see Section 8). Contains gas under pressure. Avoid breathing gas. Do not puncture or incinerate container. Use equipment rated for cylinder pressure. Close valve after each use and when empty. Protect cylinders from physical damage; do not drag, roll, slide, or drop. Use a suitable hand truck for cylinder movement.

Avoid release to the environment. Refer to special instructions/safety data sheet. Avoid contact with eyes, skin and clothing. Empty containers retain product residue and can be hazardous.

Date of issue/Date of revision : 9/16/2021 Date of previous issue 3/11 : 12/9/2017 Version: 1.01

## Section 7. Handling and storage

# Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

# Conditions for safe storage, including any incompatibilities

: Store in accordance with local regulations. Store in a segregated and approved area. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10). Cylinders should be stored upright, with valve protection cap in place, and firmly secured to prevent falling or being knocked over. Cylinder temperatures should not exceed 52 °C (125 °F). Keep container tightly closed and sealed until ready for use. See Section 10 for incompatible materials before handling or use.

# Section 8. Exposure controls/personal protection

#### **Control parameters**

**Occupational exposure limits** 

Ingredient name	Exposure limits
1,1,1,2 - tetrafluoroethane	OSHA PEL Z2 (United States, 2/2013).
	TWA: 2.5 mg/m <sup>3</sup> 8 hours. Form: Dust
	AIHA WEEL (United States, 7/2018).
	TWA: 1000 ppm 8 hours.
	ACGIH TLV (United States, 3/2019).
	TWA: 2.5 mg/m³, (as F) 8 hours.
	OSHA PEL 1989 (United States, 3/1989).
	TWA: 2.5 mg/m³, (as F) 8 hours.
	OSHA PEL (United States, 5/2018).
	TWA: 2.5 mg/m³, (as F) 8 hours.
1-Chloro-1,2,2,2-Tetrafluoroethane	AIHA WEEL (United States, 7/2018).
	TWA: 1000 ppm 8 hours.
N-Butane	NIOSH REL (United States, 10/2016).
	TWA: 1900 mg/m <sup>3</sup> 10 hours.
	TWA: 800 ppm 10 hours.
	OSHA PEL 1989 (United States, 3/1989).
	TWA: 1900 mg/m <sup>3</sup> 8 hours.
	TWA: 800 ppm 8 hours.
	ACGIH TLV (United States, 3/2019).
	Explosive potential.
	STEL: 1000 ppm 15 minutes.

# Appropriate engineering controls

**Environmental exposure controls** 

- : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
- : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### **Individual protection measures**

**Hygiene measures** 

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

#### **Eye/face protection**

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with sideshields.

Date of issue/Date of revision : 9/16/2021 Date of previous issue : 12/9/2017 Version : 1.01 4/11

# Section 8. Exposure controls/personal protection

#### **Skin protection**

**Hand protection** 

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

**Body protection** 

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection** 

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

# Section 9. Physical and chemical properties

**Appearance** 

Physical state : Gas.

Color : Not available.
Odor : Not available.
Odor threshold : Not available.
pH : Not available.

Melting point : -108°C (-162.4°F) This is based on data for the following ingredient: norflurane.

Weighted average: -144.4°C (-227.9°F)

**Boiling point** : Not available.

Critical temperature : Lowest known value: 100.9°C (213.6°F) (norflurane).

Flash point : Not available.
Evaporation rate : Not available.
Flammability (solid, gas) : Not available.
Lower and upper explosive : Not available.

(flammable) limits

Vapor pressure : Not available.

**Vapor density** : Highest known value: 3.5 (Air = 1) (norflurane). Weighted average: 3.47 (Air = 1)

Gas Density (lb/ft <sup>3</sup>) : Weighted average: 0.1

Relative density : Not applicable.
Solubility : Not available.
Solubility in water : Not available.
Partition coefficient: n- : Not available.

octanol/water

Auto-ignition temperature : Not available.

Decomposition temperature : Not available.

Viscosity : Not applicable.

Flow time (ISO 2431) : Not available.

Date of issue/Date of revision : 9/16/2021 Date of previous issue : 12/9/2017 Version : 1.01 5/11

# Section 10. Stability and reactivity

Reactivity : No specific test data related to reactivity available for this product or its ingredients.

**Chemical stability** : The product is stable.

**Possibility of hazardous** 

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

**Conditions to avoid** : No specific data.

**Incompatible materials** : No specific data.

**Hazardous decomposition** products

: Under normal conditions of storage and use, hazardous decomposition products should

not be produced.

**Hazardous polymerization** : Under normal conditions of storage and use, hazardous polymerization will not occur.

# **Section 11. Toxicological information**

#### Information on toxicological effects

#### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
1,1,1,2 - tetrafluoroethane 1-Chloro-	LC50 Inhalation Vapor LC50 Inhalation Gas.	Rat Rat	1500 g/m³ 600000 ppm	4 hours 1 hours
1,2,2,2-Tetrafluoroethane N-Butane	LC50 Inhalation Vapor	Rat	658000 mg/m³	4 hours

#### **Irritation/Corrosion**

Not available.

#### **Sensitization**

Not available.

#### **Mutagenicity**

Not available.

#### **Carcinogenicity**

Not available.

#### Reproductive toxicity

Not available.

#### **Teratogenicity**

Not available.

#### Specific target organ toxicity (single exposure)

Not available.

#### Specific target organ toxicity (repeated exposure)

Not available.

#### **Aspiration hazard**

Not available.

# Information on the likely

routes of exposure

: Not available.

Date of issue/Date of revision : 9/16/2021 6/11 Date of previous issue : 12/9/2017 Version: 1.01

Halocarbon R-416A

# Section 11. Toxicological information

#### Potential acute health effects

**Eye contact** : Contact with rapidly expanding gas may cause burns or frostbite.

Inhalation : No known significant effects or critical hazards.

**Skin contact** : Contact with rapidly expanding gas may cause burns or frostbite.

**Ingestion**: As this product is a gas, refer to the inhalation section.

#### Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data.

Inhalation : No specific data.

Skin contact : No specific data.

Ingestion : No specific data.

#### Delayed and immediate effects and also chronic effects from short and long term exposure

**Short term exposure** 

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

**Long term exposure** 

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

#### Potential chronic health effects

Not available.

General : No known significant effects or critical hazards.
 Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Teratogenicity : No known significant effects or critical hazards.
 Developmental effects : No known significant effects or critical hazards.
 Fertility effects : No known significant effects or critical hazards.

#### **Numerical measures of toxicity**

#### **Acute toxicity estimates**

Not available.

# Section 12. Ecological information

#### **Toxicity**

Not available.

#### Persistence and degradability

Not available.

#### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
1,1,1,2 - tetrafluoroethane	1.06	-	low
N-Butane	2.89	-	low

# Section 12. Ecological information

**Mobility in soil** 

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

### Section 13. Disposal considerations

#### **Disposal methods**

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Empty Airgas-owned pressure vessels should be returned to Airgas. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate container.

# **Section 14. Transport information**

	DOT	TDG	Mexico	IMDG	IATA
UN number	UN1078	UN1078	UN1078	UN1078	UN1078
UN proper shipping name	Refrigerant gas, n. o.s(1-Chloro-1,2,2,2-Tetrafluoroethane, 1,1,1,2-Tetrafluoroethane)				
Transport hazard class(es)	2.2	2.2	2.2	2.2	2.2
Packing group	-	-	-	-	-
Environmental hazards	No.	No.	No.	No.	No.

<sup>&</sup>quot;Refer to CFR 49 (or authority having jurisdiction) to determine the information required for shipment of the product."

#### **Additional information**

**TDG Classification** 

: Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.13-2.17 (Class 2).

**Explosive Limit and Limited Quantity Index 0.125** Passenger Carrying Road or Rail Index 75

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not available. to IMO instruments

Date of issue/Date of revision : 9/16/2021 : 12/9/2017 Version: 1.01 8/11 Date of previous issue

## Section 15. Regulatory information

U.S. Federal regulations : TSCA 8(a) CDR Exempt/Partial exemption: Not determined

**TSCA 12(b) one-time export**: 1-chloro-1,2,2,2-tetrafluoroethane

Clean Air Act (CAA) 112 regulated flammable substances: n-butane

Clean Air Act Section 112

(b) Hazardous Air Pollutants (HAPs)

: Not listed

**Clean Air Act Section 602** 

**Class I Substances** 

: Not listed

Clean Air Act Section 602
Class II Substances

: Listed

**DEA List I Chemicals** 

(Precursor Chemicals)

: Not listed

**DEA List II Chemicals** (Essential Chemicals)

: Not listed

**SARA 302/304** 

**Composition/information on ingredients** 

No products were found.

SARA 304 RQ : Not applicable.

**SARA 311/312** 

**Classification**: Refer to Section 2: Hazards Identification of this SDS for classification of substance.

**SARA 313** 

	Product name	CAS number	%
Form R - Reporting requirements	1-chloro-1,2,2,2-tetrafluoroethane	2837-89-0	39.5
Supplier notification	1-chloro-1,2,2,2-tetrafluoroethane	2837-89-0	39.5

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

#### **State regulations**

Massachusetts : The following components are listed: BUTANE

New York : None of the components are listed.

New Jersey : The following components are listed: FLUORIDES; 2-CHLORO-

1,1,1,2-TETRAFLUOROETHANE; ETHANE, 2-CHLORO-1,1,1,2-TETRAFLUORO-;

**BUTANE** 

Pennsylvania : The following components are listed: BUTANE

California Prop. 65

This product does not require a Safe Harbor warning under California Prop. 65.

#### International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

#### **Montreal Protocol**

Ingredient name	Status
	Annex C, Group I
HFC-134a	Annex F, Group I

#### **Stockholm Convention on Persistent Organic Pollutants**

Not listed.

#### **Rotterdam Convention on Prior Informed Consent (PIC)**

Not listed.

# Section 15. Regulatory information

#### **UNECE Aarhus Protocol on POPs and Heavy Metals**

Not listed.

#### **Inventory list**

Australia : All components are listed or exempted.

Canada : Not determined.

China : All components are listed or exempted.Europe : All components are listed or exempted.

Japan : Japan inventory (ENCS): All components are listed or exempted.

Japan inventory (ISHL): All components are listed or exempted.

New Zealand : All components are listed or exempted.
Philippines : All components are listed or exempted.
Republic of Korea : All components are listed or exempted.
Taiwan : All components are listed or exempted.

Thailand : Not determined.


Turkey : Not determined.

**United States** : All components are active or exempted.

Viet Nam : Not determined.

### Section 16. Other information

#### **Hazardous Material Information System (U.S.A.)**



Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

#### **National Fire Protection Association (U.S.A.)**



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

#### Procedure used to derive the classification

Classification	Justification
	On basis of test data Calculation method

### Section 16. Other information

#### **History**

Date of printing : 9/16/2021

Date of issue/Date of : 9/16/2021

revision

Date of previous issue : 12/9/2017 Version : 1.01

**Key to abbreviations** : ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973

as modified by the Protocol of 1978. ("Marpol" = marine pollution)

UN = United Nations

**References** : Not available.

Other special considerations

WARNING: Contains (Chlorotetrafluoroethane (Freon 124), a substance which harms the public health and environment by destroying ozone in the upper atmosphere.

#### **Notice to reader**

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Date of issue/Date of revision : 9/16/2021 Date of previous issue : 12/9/2017 Version : 1.01 11/11