InTech[®] Combustion Analyzer For Residential Applications





Image: Second Second



DESCRIPTION

Bacharach's InTech[®] is the perfect tool for entry-level residential HVAC technicians providing readings for O₂, CO, CO₂, Combustion Efficiency and Temperature. The InTech[®] is available with precalibrated, B-Smart[®] gas sensors to minimize downtime and maintenance costs. The Combustion mobile app (available for Android & iOS) allows users to create and send customizable combustion reports on-site.

FEATURES	BENEFITS
Readings for O ₂ , CO, CO ₂ , Combustion Efficiency & Temperature	All-in-one instrument makes combustion tuning fast and simple.
Combustion App	Quickly create custom reports with comments and send via email (available for Android & iOS).
Automatic Sensor Protection	Protects sensors in the toughest combustion environments, extending life
IR Printer with Magnet	Print combustion and emissions reports in the field
Ambient CO Monitor	Check for dangerous levels of ambient CO
Precalibrated, B-Smart® Sensors	Quick and easy sensor replacement in the field & reduced downtime (doesn't require cal. gas)



Automatic delivery of precalibrated sensors to your door to eliminate field calibration and minimize maintenance

HOW TO CONTACT US:

US Customer Service: +1 724 334 5000 EU Customer Service: +353 1 284 6388 CAN Customer Service: +1 905 882 8985 Fyrite[®] and InTech[®] are trademarks of Bacharach, Inc.

mybacharach.com

FOR MORE INFO:

Scan the QR code to learn more about the Fyrite[®] InTech and other Bacharach products.



SPECIFICATIONS	DESCRIPTION
O ₂	20.9%
СО	0 to 2,000 ppm
Stack Temperature	-4 to 1,202°F (-20 to 650°C)
Ambient Temperature	-4 to 212°F (-20 to 100°C)
Fuels ¹	Natural Gas, Oil 2 / 6, Kerosene, Propane, Butane, LPG, B5, KOKS, LEG and Biofuel

PRODUCT DETAILS	DESCRIPTION
Display	2.7" (72 mm) backlit, monochrome LCD
Display Languages	English, Spanish, French
Power	4 × AA Disposable Alkaline Batteries ≈ 15 hours
Size (H \times W \times D)	8.0" × 3.6" × 2.3". (20.3 × 9.1 × 5.8 cm)
Weight	1 lb. (0.45 kg) including batteries
Memory	10 locations
Communications	USB 2.0 (mini-B), IrDA
Approvals	CE, EN 50379-1 & -3
Warranty	2 years (including sensors)

PART NUMBERS *	DESCRIPTION
0024-8510	Fyrite [®] InTech [®] O_2 Analyzer (analyzer with O_2 sensor, 12" probe, 6" sample hose assembly, water trap, particulate filter and soft carrying case)
0024-8511	Fyrite [®] InTech [®] (analyzer with O_2 and CO sensors, 12" probe, 6" sample hose assembly, water trap, particulate filter and soft carrying case)
0024-8523	Fyrite® InTech® with Protective Case (protective rubber boot and rugged protective carrying case)
0024-8512	Fyrite [®] InTech [®] with Protective Case & Reporting Kit (IrDA wireless printer, USB cable and Fyrite User Software)

* Siegert configurations available.

