

## EXTREME SELF LIGHTING TORCH KITS

Extreme Swirl Technology delivers high heat, super fast, reducing brazing time and fuel consumption. All air acetylene kits include gauge guards and cylinder wrench. Our best line of self-lighting torch kits are available in either valve rear or valve forward configurations. Improved design features quick-disconnect handles and tips, replaceable tips and color coded "O" rings for quick gas identification.



### PL-5ADLX-MC (0386-0832)

#### COMPONENTS

- AR-MC (CGA 200) Regulator
- G-4 Handle
- AH-12 Hose
- PL-5A Tip
- Soft solders to 1-1/2" (40 mm)
- Silver brazes to 3/4" (20 mm)
- "MC" Tank Connections
- Instruction Manual



### PL-8ADLX-MC (0386-0834)

#### COMPONENTS

- AR-MC (CGA 200) Regulator
- G-4 Handle
- AH-12 Hose
- PL-8A Tip
- Soft solders to 2" (50 mm)
- Silver brazes to 1" (30 mm)
- "MC" Tank Connections
- Instruction Manual

Kit No.	Model	Soft Solders	Silver Brazes	Regulator	Handle	Hose	Tip	Tank Connection	Valve Position
PL-5ADLX-MC	0386-0832	1-1/2" 40 mm	3/4" 20 mm	AR-MC (CGA-200)	G4	AH-12	PL-5A	MC	Rear
PL-5ADLX-B	0386-0833	1-1/2" 40 mm	3/4" 20 mm	AR-B (CGA-520)	G4	AH-12	PL-5A	B	Rear
PL-8ADLX-MC	0386-0834	2" 50 mm	1" 30 mm	AR-MC (CGA-200)	G4	AH-12	PL-8A	MC	Rear
PL-8ADLX-B	0386-0835	2" 50 mm	1" 30 mm	AR-B (CGA-520)	G4	AH-12	PL-8A	B	Rear
PL-12ADLX-B	0386-0836	4" 90 mm	2" 5 mm	AR-B (CGA-520)	G4	AH-12	PL-12A	B	Rear
PLF-5ADLX-MC	0386-0864	1-1/2" 40 mm	3/4" 20 mm	AR-MC (CGA-200)	PLF-A5	AH-12	PL-5A	MC	Forward
PLF-5ADLX-B	0386-0865	1-1/2" 40 mm	3/4" 20 mm	AR-B (CGA-520)	PLF-A5	AH-12	PL-5A	B	Forward
PLF-8ADLX-MC	0386-0866	2" 50 mm	1" 30 mm	AR-MC (CGA-200)	PLF-A5	AH-12	PL-8A	MC	Forward
PLF-8ADLX-B	0386-0867	2" 50 mm	1" 30 mm	AR-B (CGA-520)	PLF-A5	AH-12	PL-8A	B	Forward
PLF-12ADLX-B	0386-0868	4" 90 mm	2" 50 mm	AR-B (CGA-520)	PLF-A5	AH-12	PL-12A	B	Forward
PL-12ASTD	0386-0828	4" 90 mm	2" 50 mm	-	G4	-	PL-12A	-	Rear