

## EXTREME™ SELF LIGHTING REPLACEMENT TIPS

Increase the range of your torch kit with additional self lighting tips. All TurboTorch tips feature an orifice screw that can be easily removed for simple cleaning or replacement, extending the life of the tip.



**PL-3A**  
(0386-0874)



**3A-TE**  
(0386-1059)



**PL-5A**  
(0386-0818)



**5A-TE**  
(0386-1064)



**PL-8A**  
(0386-0819)



**8A-TE**  
(0386-1065)



**PL-12A**  
(0386-0820)



**12A-TE**  
(0386-1066)

Tip No.	Tip Size		Gas Flow		Soft Solder		Silver Solder		Replacement Orifice	Replacement Tip	BTU
	IN.	MM	@14 PSI SCFH	(0.9 BAR) M3/HR	IN.	MM	IN.	MM			
PL-3A	3/16	5.0	3.6	.31	1/4-1	10-25	1/8-1/2	3-12	OR-A3 0386-1001	3A-TE	1,280
PL-5A	1/4	6.4	5	.42	3/4-1 1/2	20-40	1/4-3/4	10-20	OR-A8 0386-1003	5A-TE	2,080
PL-8A	5/16	7.9	7	.59	1-2	25-50	1/2-1	15-30	- 0305-0511	8A-TE	2,520
PL-12A	3/8	9.5	9	.76	2-4	50-90	1-2	25-50	OR-T-6 0386-1024	12A-TE	3,360