



7702G

7702G SERIES • GAS BALL VALVE • TWO-PIECE BODY FORGED BRASS

Item No.	Size	Connection	Inner Qty.	Master Qty.	Each Wt.	
STYLE 7702G – LEVER HANDLE						
110-122	3/8"	FPT x FPT	10	100	0.29	<ul style="list-style-type: none"> • 200 PSI • -20°F - 300°F temperature range • Quarter-turn lever handle for positive on/off operation • Coated aluminum handle for corrosion and solvent resistance • Multi-directional flow • Two-piece body design
110-123HC	1/2"	FPT x FPT	-	20	0.35	
110-124HC	3/4"	FPT x FPT	-	10	0.53	
110-125	1"	FPT x FPT	6	30	0.85	

- Chrome-plated brass ball
- CSA - ANSI Z21.15 (1/2 PSIG)
- ANSI/ASME B16.44 (5G)
- UL listed
- Threaded ends comply with ANSI B1.20.1



7702GE

7702G SERIES • GAS BALL VALVE • TWO-PIECE BODY FORGED BRASS

Item No.	Size	Connection	Inner Qty.	Master Qty.	Each Wt.	
STYLE 7702GE – LEVER HANDLE						
110-223C	1/2"	FPT x FPT	10	100	0.33	<ul style="list-style-type: none"> • 200 PSI • -20°F - 300°F temperature range • Quarter-turn lever handle for positive on/off operation • Coated aluminum handle for corrosion and solvent resistance • Multi-directional flow • Two-piece body design
110-224C	3/4"	FPT x FPT	10	100	0.48	
110-225	1"	FPT x FPT	6	36	0.91	

- Chrome-plated brass ball
- CSA - ANSI Z21.15 (1/2 PSIG)
- ANSI/ASME B16.44 (5G)
- UL listed
- Threaded ends comply with ANSI B1.20.1



* Please call for availability.