



7701GSTF

7701G SERIES • GAS BALL VALVE • ONE-PIECE BODY • SIDE TAPPED FORGED BRASS

Item No.	Size	Connection	Inner Qty.	Master Qty.	Each Wt.
----------	------	------------	------------	-------------	----------

STYLE 7701GSTF – FLARE X FLARE

116-552	3/8"	FLARE x FLARE	10	100	0.42
116-553	1/2"	FLARE x FLARE	10	100	0.39

- 200 PSI
- -20°F - 300°F temperature range
- Quarter-turn lever handle for positive on/off operation
- Coated aluminum handle for corrosion and solvent resistance
- Multi-directional flow
- One-piece body for leak resistance and long valve life
- Chrome-plated brass ball

- 1/8" NPT side tap for pressure test, drain, line extension, and more (plug included)
- Save on parts & labor by attaching manometer to line testing at valve
- CSA - ANSI Z21.15 (1/2 PSIG)
- ANSI/ASME B16.44 (5G)
- Threaded ends comply with SAE J513



7701GFL

7701G SERIES • GAS BALL VALVE • ONE-PIECE BODY • FLARE END FORGED BRASS

Item No.	Size	Connection	Inner Qty.	Master Qty.	Each Wt.
----------	------	------------	------------	-------------	----------

STYLE 7701GFL – FLARE X FLARE

116-502	3/8"	FLARE x FLARE	10	100	0.37
116-503	1/2"	FLARE x FLARE	10	100	0.34
116-504	5/8"	FLARE x FLARE	10	100	0.52

- 200 PSI
- -20°F - 300°F temperature range
- Quarter-turn lever handle for positive on/off operation
- Coated aluminum handle for corrosion and solvent resistance
- Multi-directional flow

- One-piece body for leak resistance and long valve life
- Chrome-plated brass ball
- CSA - ANSI Z21.15 (1/2 PSIG)
- ANSI/ASME B16.44 (5G)
- Threaded flare ends comply with SAE J513

