



21D64-2

## HOTROD™ SERIES UNIVERSAL NITRIDE IGNITOR UPGRADES

120V nitride upgrade kits for conversion of silicon carbide (flat or spiral).

### FEATURES

- HotRod™ replaces over 170 ignitors; HotRod EX™ replaces over 260 ignitor models
- Robust nitride ignitor design for longer life and fewer callbacks – 5-year warranty
- Nitride ignitors with 14.5" and 15.5" lead-stripped ends
- Universal and standard mounting brackets and 2 ceramic wire nuts
- Replaces most silicon carbide ignitors, including many Carborundum™ models

### SPECIFICATIONS

Operating Voltage.....	102-132 VAC, 60 Hz
Max. Load Current .....	3.0 A @ 132 VAC, 25°C
Warmup Time .....	21D64-2: 17 sec. minimum
.....	21D64-44: 8 sec. minimum
Temperature Rating Lead Insulation .....	250°C

### HOTROD™ 21D64 SERIES UNIVERSAL IGNITOR UPGRADES

DESCRIPTION	LEAD LENGTH	MODEL NUMBER	ITEM NUMBER
HotRod Kit includes 120V nitride ignitor, 2 brackets (one universal), 15.5" lead-stripped ends, ceramic wire nuts and mounting screw	15.5"	21D64-2	21D64 002
HotRod 5-pack contains 5 single-pack ignitor kits	15.5"	21D64-5PK	21D64-5PK
HotRod EX Kit includes 120V nitride ignitor, 2 brackets (one universal), 14.5" lead-stripped ends, ceramic wire nuts and mounting screw	14.5"	21D64-44	21D64-44

### FLAME SENSOR AND HOT ROD COMBO

DESCRIPTION	LEAD LENGTH	MODEL NUMBER	ITEM NUMBER
HotRod Combo, universal ignitor and flame sensor	15.5" / 30"	21D64C-843	21D64C-843

