

#### M12 FLEL

#### 1/2" Hammer Drill/Driver Kit

2504-22 (2504-20 Tool-Only)

#### **Specifications:**

Peak Torque	350 in-lbs
RPM	0 – 1,700
BPM	0 – 25,500
Chuck Type	1/2" Metal Single Sleeve – Ratcheting Chuck
Length / Weight	6.6" / 2.3 lbs

**Includes:** (1) M12<sup>™</sup> REDLITHIUM<sup>™</sup> XC4.0 Battery Pack. (1) M12™ REDLITHIUM™ CP2.0 Battery Pack, Belt Clip, Charger, Carrying Case

### M12™ 3/8" Hammer **Drill/Driver Kit**

2408-22 (2408-20 Tool-Only)

#### **Specifications:**

Peak Torque	275 in-lbs
RPM	0 - 400 / 0 - 1,500
BPM	0 – 22,500
Chuck Type	3/8" Metal Single Sleeve
Length / Weight	7.5" / 2.7 lbs

**Includes:** (2) M12<sup>™</sup> REDLITHIUM<sup>™</sup> CP1.5 Battery Packs. Belt Clip, Charger, Carrying Case

# M12 FUEL 1/2" Drill/Driver Kit 2503-22 (2503-20 Tool-Only) Specifications:

Peak Torque	350 in-lbs
RPM	0 – 1,700
Chuck Type	1/2" Metal Single Sleeve – Ratcheting Chuck
Length / Weight	6.6" / 2.3 lbs

**Includes:** (1) M12<sup>™</sup> REDLITHIUM<sup>™</sup> XC4.0 Battery Pack, (1) M12™ REDLITHIUM™ CP2.0 Battery Pack, Belt Clip, Charger, Carrying Case

### M12 FLEL Installation **Drill/Driver Kit**

2505-22 (2505-20 Tool-Only)

#### Specifications:

Specification	13.	
Max Torque	300 in-lbs	
RPM (2-Mode)	0 - 400 / 0 - 1,600	
Attachments	3/8" Metal Chuck, 1/4" Hex, Offset and Right	Angle
Length / Weight	5.1" / 2.0 lbs	

**Includes:** (2) M12™ REDLITHIUM™ CP2.0 Battery Packs, (4) Attachments (3/8" Metal Chuck, 1/4" Hex, Offset and Right Angle), Belt Clip, Charger, Compartmentalized Contractor Bag

### M12™ 3/8" **Drill/Driver Kit**

2407-22 (2407-20 Tool-Only)

Specifications:		
Peak Torque	275 in-lbs	
RPM	0 - 400 / 0 - 1,500	
Chuck Type	3/8" Metal Single Sleeve	
Length / Weight	7.4" / 2.5 lbs	

**Includes:** (2) M12<sup>™</sup> REDLITHIUM<sup>™</sup> CP1.5 Battery Packs, Belt Clip, Charger, Carrying Case

# M12™ 3/8" Right **Angle Drill/Driver Kit**

2415-21 (2415-20 Tool-Only)

### **Specifications:**

-	
Peak Torque	100 in-lbs
RPM	0 – 800
Clutch Settings	11 Settings plus Drill Mode
Chuck Type	3/8" Single Sleeve
Head Profile	3.8"
Weight	2.4 lbs

**Includes:** (1) M12<sup>™</sup> REDLITHIUM<sup>™</sup> CP1.5 Battery Pack, Charger, Soft Carrying Case

### 1/4" Hex 2-Speed Screwdriver Kit

2402-22 (2402-20 Tool-Only)

#### Specifications:

Peak Torque	325 in-lbs
RPM	0 - 450 / 0 - 1,700
Chuck Type	1/4" Hex Quick Change
Length / Weight	6.6" / 2.0 lbs

Includes: (2) M12™ REDLITHIUM™ CP2.0 Battery Packs, Belt Clip, Charger, Carrying Case

# M12™ 1/4" Hex 2-Speed **Screwdriver Kit**

2406-22 (2406-20 Tool-Only)

#### **Specifications:**

Peak Torque	275 in-lbs
RPM	0 - 400 / 0 - 1,500
Chuck Type	1/4" Hex Quick Change
Length / Weight	6.8" / 1.8 lbs

**Includes:** (2) M12<sup>™</sup> REDLITHIUM<sup>™</sup> CP1.5 Battery Packs, Belt Clip, Charger, Carrying Case

#### M12™ 1/4" Hex **Screwdriver Kit**

2401-22 (2401-20 Tool-Only)

### Specifications:

Peak Torque	175 in-lbs
RPM	0 – 500
Chuck Type	1/4" Hex Quick Change
Length / Weight	6.5" / 2.0 lbs

**Includes:** (2) M12<sup>™</sup> REDLITHIUM<sup>™</sup> CP1.5 Battery Packs, Belt Clip, Charger, Soft Carrying Case

# M12 FUEL 1/4" Hex Impact Driver Kit

2553-22 (2553-20 Tool-Only)

#### Specifications:

Specifications.	
Fastening Torque	1,300 in-lbs
IPM	0 – 4,000
RPM	0 – 3,300
Chuck Type	1/4" Hex Quick Change
Length / Weight	5.1" / 1.8 lbs

**Includes:** (2) M12<sup>™</sup> REDLITHIUM<sup>™</sup> CP2.0 Battery Packs, Belt Clip, Charger, Carrying Case



# **SURGE™ 1/4" Hex Hydraulic Driver Kit**

2551-22 (2551-20 Tool-Only)

#### **Specifications:**

Sustained Fastening Torque	450 ft-lbs
IPM	0 – 3,400
RPM	0 – 3,200
Chuck Type	1/4" Hex Quick Change
Length / Weight	5.2" / 2.4 lbs

**Includes:** (2) M12™ REDLITHIUM™ CP2.0 Battery Packs, Belt Clip, Charger, Contractor Bag

#### M12™ 1/4" Hex Impact **Driver Kit**

2462-22 (2462-20 Tool-Only)

#### **Specifications:**

Fastening Torque	1,000 in-lbs
IPM	0 – 3,300
RPM	0 – 2,500
Chuck Type	1/4" Hex
Length / Weight	6.5" / 2.3 lbs

**Includes:** (2) M12<sup>™</sup> REDLITHIUM<sup>™</sup> CP1.5 Battery Packs, Belt Clip, Charger, Carrying Case

#### M12™ 1/4" Hex Right Angle **Impact Driver Kit**

2467-21 (2467-20 Tool-Only)

# **Specifications:**

Fastening Torque	600 in-lbs
IPM	0 – 3,300
RPM	0 - 2,450
Chuck Type	1/4" Hex
Head Profile	1.4"
Weight	2.6 lbs

**Includes:** (1) M12<sup>™</sup> REDLITHIUM<sup>™</sup> CP1.5 Battery Pack, Charger, Soft Carrying Case

### 1/2" Stubby Impact Wrench Kit

2555-22, 2555P-22 (2555-20 Tool-Only)

### Specifications:

opeonione.		
Peak Torque	250 ft-lbs	
IPM	0 – 3,200	
RPM	0 – 2,700	
Anvil Type	1/2" Friction Ring	
Length / Weight	4.9" / 2.1 lbs	

Includes: 2555-22 1/2" Stubby Impact Wrench: 2555P-22 1/2" Stubby Impact Wrench w/ Pin Detent; **All Kits Include:** (1) M12™ REDLÍTHIÚM™ XC4.0 Battery Pack, (1) M12™ REDLÍTHIUM™ CP2.0 Battery Pack, Belt Clip, Charger, Soft Carrying Case



# 3/8" Stubby Impact Wrench Kit

2554-22 (2554-20 Tool-Only) Specifications:

-	
Peak Torque	250 ft-lbs
IPM	0 – 3,200
RPM	0 – 2,700
Anvil Type	3/8" Friction Ring
Length / Weight	4.8" / 2.1 lbs

**Includes:** (1) M12<sup>™</sup> REDLITHIUM<sup>™</sup> XC4.0 Battery Pack, (1) M12™ REDLITHIUM™ CP2.0 Battery Pack, Belt Clip, Charger, Soft Carrying Case

# 

# 1/4" Stubby Impact Wrench Kit

2552-22 (2552-20 Tool-Only)

#### Specifications:

Peak Torque	100 ft-lbs
IPM	0 – 4,300
RPM	0 – 3,200
Anvil Type	1/4" Friction Ring
Length / Weight	5.1" / 1.8 lbs

**Includes:** (1) M12<sup>™</sup> REDLITHIUM<sup>™</sup> XC4.0 Battery Pack, (1) M12™ REDLITHIUM™ CP2.0 Battery Pack, Belt Clip, Charger, Soft Carrying Case

# 

# 3/8" Impact Wrench Kit

2454-22 (2454-20 Tool-Only)

### Specifications:

	Peak Torque	117 ft-lbs
	IPM	0 – 3,500
	RPM (2-Mode)	0 - 1,200 / 0 - 2,650
	Anvil Type	3/8" Friction Ring
	Length / Weight	6.5" / 2.4 lbs

**Includes:** (2) M12<sup>™</sup> REDLITHIUM<sup>™</sup> CP2.0 Battery Packs, Belt Clip, Charger, Carrying Case

# M12™ 3/8" Impact Wrench Kit

2463-22 (2463-20 Tool-Only)

# Specifications:

	1 car rorque	100 11 103
	IPM	0 – 3,300
	RPM	0 – 2,500
	Anvil Type	3/8" Friction Ring
	Length / Weight	6.5" / 2.3 lbs

**Includes:** (2) M12<sup>™</sup> REDLITHIUM<sup>™</sup> CP2.0 Battery Packs, Belt Clip, Charger, Carrying Case

# M12™ 1/4" Impact Wrench Kit

2461-22 (2461-20 Tool-Only)

# Specifications:

Peak Torque	38 ft-lbs
IPM	0 – 3,800
RPM	0 – 2,500
Anvil Type	1/4" Friction Ring
Length / Weight	6.0" / 2.1 lbs

**Includes:** (2) M12<sup>™</sup> REDLITHIUM<sup>™</sup> CP1.5 Battery Packs, Belt Clip, Charger, Carrying Case





