

Capacitor Start Belted Fan & Blower Open Drip Proof, Resilient Base




APPLICATIONS:

Designed to meet manufacturer's requirements for belted fans and blowers.

FEATURES:

- 40°C Ambient
- Class A Insulation
- Reversible Rotation
- Suitable For All Angle Operation (Within Blower Housing)
- Automatic Reset Thermal Overload Protector (unless noted)
- Threaded Conduit Hole, Except 299
- 208v will not be marked on DOE regulated spread-voltage motors. Refer to online data
- **Discount Symbol: DS-3HAC**



HP	RPM	Voltage	Catalog Number	List	Bearings	NEMA Frame	Amps	Shaft N	Shaft U	Protector	Total C	SF	Ship Wt.	Notes
1/4	1140	115/208-230	BD14CA3J9	◆	Ball	56	6.4/3.0-3.2	1.9	0.625	Auto	11.31	1.35	32	
1/3	1725	115/230	180	◆	Ball	48	6.0/3.0	1.5	0.500	Auto	9.9	1.35	18	
1/2	3450	115/208-230	298	◆	Ball	48	8.6/4.3	1.5	.500	Auto	9.9	1.25	16	
	1725	100-120/200-240	6309	◆	Ball	56	6.3-5.6/3.1-2.8	1.9	0.625	Auto	10.8	1.25	26	18,24,98
	1725	115/208-230	1790	◆	Ball	56	7.4/3.7	1.9	.625	Auto	9.3	1.25	27	
3/4	3450	115/208-230	430	◆	Ball	48	9.2/4.6	1.5	.500	Auto	10.4	1.25	19	
	1725	100-120/200-240	6313	◆	Ball	56	9.2-8.4/4.6-4.2	1.9	0.625	Auto	11.3	1.25	32	18,24,98
	1725	115/208-230	1893	◆	Ball	56	11.4/5.7	1.9	0.625	Auto	10.8	1.25	27	
1	3450	115/208-230	431	◆	Ball	48Z	11.6/5.8	1.9	.625	Auto	11.3	1.25	13	
	1725	100-120/200-240	6317	◆	Ball	56	12.3-10.8/6.2	1.9	0.625	Auto	12.3	1.15	38	18,24,98
	1725	115/230	3187C	◆	Ball	56	14.0/7.0	1.9	.625	Auto	11.8	1.25	23	80
	1725	115/208-230	1769	◆	Ball	56	14.0/7.0	1.9	0.625	Auto	11.8	1.25	30	
1-1/2	3450	115/230	299	◆	Ball	56	17.2/9.0	1.9	.625	Auto	11.9	1.15	33	
	1725	115/208-230	4242	◆	Ball	56	22.4/11.2	1.9	0.625	Auto	12.8	1.15	40	
2	3450	115/208-230	399	◆	Ball	56	18.4/10.1-9.2	1.9	0.625	Auto	12.8	1.2	37	

◆ Refer to Motorboss for Pricing

Note 18: Incorporates Run Capacitor
Note 24: Automatic Reset Thermal Overload Protector

Note 80: Canadian Standard — Connected CCWLE (Reversible)
Note 98: 50/60 Hz Motor

