

## MULTI-PURPOSE LEAK SEALER

- Reliable rubberized coating
- Quick and economical answer to repair troublesome leaks
- Temperature range -10°F to 250°F
- Stays flexible and won't freeze or sag
- Contains no CFC's
- Dries in 20 to 30 minutes
- Ideal for sealing out both rust and corrosion
- Can be painted

### Description

Pan-Spray is an effective, easy-to-use water proof rubberized coating that won't chip, flake, or peel. It's ideal for sealing out rust and corrosion as well as repairing leaky condensate pans, cooling towers, swamp coolers, roofing, gutters, and down spouts. Pan Spray is the perfect solution for emergency and permanent repair.

### Application

It is a quick, easy and economical repair on troublesome leaks. Use on condensate pans, swamp coolers, humidifier pans, plumbing and pipe fixtures, roofing, downspouts or gutters.

## Aerosol Products

### Pan-Spray™



### Directions for Use

Shake for a minimum of 30 seconds. Apply to clean surface. Spray surface with short, even strokes from a distance of 10 to 12 inches. Apply until thoroughly coated. For large holes or cracks apply Pan-Spray around edge of leak, then place a mesh material over leak before final coating is applied.

After use, clean spray valve tip by inverting can and spraying until only gas comes out. Cleanup with mineral spirits or paint thinner.

### Packaging

- |                     |                |
|---------------------|----------------|
| 16 ounce can -white | <b>4296-50</b> |
| 16 ounce can -white | <b>4296-51</b> |

Read and understand the product's label and Material Safety Data Sheet ("MSDS") for precautionary and first aid information.

The MSDS is available on the Nu-Calgon website at [www.nucalgon.com](http://www.nucalgon.com).

