



105-414

## STOP & WASTE VALVE • 100 PSI PVC

Item No.	Size	Connection	Inner Qty.	Master Qty.	Each Wt.
<b>SOLVENT – NO LEAD</b>					
105-413	1/2"	C x C	12	72	0.15
105-414	3/4"	C x C	12	72	0.20

- Rated for 100 PSI at 73°F
- Rising stem for positive open and close operation
- For use with cold water
- Not for use with compressed air
- Plug allows draining of non-pressure side of valve when closed

- Solvent ends comply with ASTM 2866
- Certified to NSF 61-G
- "Lead-Free" Compliant



106-005



106-005NL

## GLOBE VALVE • HARD SEAT • 200 PSI BRASS

Item No.	Size	Connection	Inner Qty.	Master Qty.	Each Wt.
<b>THREADED</b>					
106-001	1/4"	FPT x FPT	10	100	0.50
106-002	3/8"	FPT x FPT	10	100	0.57
106-003	1/2"	FPT x FPT	10	100	0.57
106-004	3/4"	FPT x FPT	5	60	0.75
106-005	1"	FPT x FPT	5	40	1.12
106-006	1-1/4"	FPT x FPT	5	30	1.94
106-007	1-1/2"	FPT x FPT	4	24	2.38
106-008	2"	FPT x FPT	4	12	4.03

- 200 PSI WOG/125 PSI WSP
- Rising stem for positive open and close operation

- Large flow area
- Heavy six-point cast-iron handle
- Threaded ends comply with ANSI B1.20.1

Item No.	Size	Connection	Inner Qty.	Master Qty.	Each Wt.
<b>THREADED – NO LEAD</b>					
106-001NL	1/4"	FPT x FPT	10	100	0.5
106-002NL	3/8"	FPT x FPT	10	100	0.57
106-003NL	1/2"	FPT x FPT	10	100	0.57
106-004NL	3/4"	FPT x FPT	5	60	0.75
106-005NL	1"	FPT x FPT	5	40	1.12
106-006NL	1-1/4"	FPT x FPT	5	30	1.94
106-007NL	1-1/2"	FPT x FPT	4	24	2.38

- 200 PSI WOG/125 PSI WSP
- Rising stem for positive open and close operation
- Large flow area

- Heavy six-point cast-iron handle
- Threaded ends comply with ANSI B1.20.1
- "Lead-Free" Compliant



\* Please call for availability.