

RESCUE® Motors Permanent Split Capacitor Condenser Fan 5.6" Diameter, Totally Enclosed Air Over (TEAO)





APPLICATIONS:

Commercial and Residential Condensing Units. Can replace a range of horsepower application and a variety of mounting styles.

FEATURES:

- High 158°F (70°C) Or 140°F (60°C) Ambient Designs
- Automatic Reset Thermal Overload Protector
- Designed For Use With 370V Capacitors
- Special Treated Rotor For Corrosion Protection
- Includes Lead End Mounting Holes For Rheem®† Or Trane®† Units
- 48" Leads
- Extended Mounting Studs
- Ball Bearings
- Reversible Rotation
- High Efficiency Design
- Continuous Duty, Air Over
- Ball Bearings
- Reversible Rotation
- Discount Symbol: DS-3HAC



**RESCUE® Condenser Motors available
in 158°F (70°C) ambient ratings!**

HP	RPM	Volts	Catalog Number	List Price	Max. Ambient	Speed Tap	Cap. MFD @ 208V	Cap. MFD @ 230V	Amps	Shaft N	Shell XI	Total C	Ship Wgt.	Notes
1/3	825	208-230	5464	\$135	140°F(60°C)	High	10	7.5	1.9	5	5.3	10.3	18	1
1/4					High	10	7.5	1.5						
1/5					Low	10	7.5	1.2						
1/6					Low	10	7.5	1.0						
1/3	825	208-230	5464H	\$139	158°F(70°C)	High	10	7.5	1.9	5	5.3	10.3	18	1
1/4					High	10	7.5	1.5						
1/5					Low	10	7.5	1.2						
1/6					Low	10	7.5	1.0						
1/3	1075	208-230	5462	\$109	140°F(60°C)	High	7.5	5	2.6	5	4.6	9.6	14	1
1/4					High	7.5	5	2.5						
1/5					Low	7.5	5	2.0						
1/6					Low	7.5	5	1.8						
1/3	1075	208-230	5462H	\$114	158°F(70°C)	High	7.5	5	2.6	5	4.6	9.6	14	1
1/4					High	7.5	5	2.5						
1/5					Low	7.5	5	2.0						
1/6					Low	7.5	5	1.8						
1/2	1075	208-230	5465	\$138	140°F(60°C)	High	12.5	10	3.0	5	5.3	10.3	19	1
1/3					High	12.5	10	2.2						
1/4					Low	12.5	10	1.6						
1/5					Low	12.5	10	1.3						

Note 1 Side Shell & Lead End Mounting Screws Included In Carton

† All non-Emerson Electric Co. marks shown within this document are properties of their other respective owners.