

Pliers
Strippers, Cutters, and Crimpers
Drivers and Wrenches
Conduit Tools and Measurement
Tool Kits
Safety, PPE and Comfort
Jobsite Accessories
Tool Storage
Voice/Data/Video
Test and Measurement
Power Tools and Accessories
Lifting, Pulling, and Structural

Screw-Holding Screwdrivers

- Starts and drives screws with one hand when working in hard-to-reach spaces



| Cat. No. | Tip Type | Shank Type | Shank Length | Overall Length |
|----------|-----------------------|------------|--------------|------------------|
| 32215 | 1/4" (6.4 mm) Cabinet | Round | 7" (17.8 cm) | 11.25" (28.6 cm) |
| 32216 | #2 Phillips | Round | 7" (17.8 cm) | 11.25" (28.6 cm) |



32215

Terminal Block Screwdriver

Includes core Cushion-Grip™ Screwdriver features plus:

- Provides exact fit for terminal block screws
- Tip is up to 19% stronger than competitors and provides 76% higher torque value than the required ASME B107 Standard



| Cat. No. | Tip Type | Shank Type | Shank Length | Overall Length |
|----------|-----------------------|------------|--------------|-----------------|
| 612-4 | 1/8" (3.2 mm) Cabinet | Round | 4" (10.2 cm) | 7.75" (19.7 cm) |



612-4

Slotted Screw Holding Driver, 3/16", 1/4", 5/16"

- Slotted screw-holding feature mechanically holds screws to work where stainless steel is required
- Essential when working with non-magnetic screws and installing overhead fixtures
- Durable to start and drive screws with 1 tool
- Engage the screw holding feature with just the slide of your thumb
- Cushion-Grip™ handle for greater torque and comfort
- Helps prevent dropping slotted screws on the jobsite
- Built to handle the tough jobs with ease

NEW ★



6013K



6024K



6026K



| Cat. No. | Tip Type | Shank Type | Shank Length | Overall Length |
|----------|------------------------|------------|---------------|-------------------|
| ★ 6013K | 3/16" (4.8 mm) Slotted | Round | 3" (7.62 cm) | 5.78" (14.7 cm) |
| ★ 6024K | 1/4" (6.4 mm) Slotted | Round | 4" (10.2 cm) | 8.38" (21.3 cm) |
| ★ 6026K | 5/16" (7.9 mm) Slotted | Round | 6" (15.24 cm) | 11.19" (28.42 cm) |

Slotted Screw Holding Driver Kit

| | |
|----------|---|
| ★ 85153K | ● |
| | ● |
| | — |

