

**CONDUIT, FITTINGS, CABLE cont'd**

**Aluminum Armored MC Cable**

90° C Rated aluminum metal clad cable system. THHN solid copper with specially compounded heat-resistant U.L. Listed insulation and jacket. Flexible interlocked aluminum armor. Extremely durable – withstands severe handling. U.L. Listed #4. Conforms to NEC article 333.



CATALOG NO.	DESCRIPTION	UOM	ORDER MULTIPLE
<b>640-122</b>	12-2 Aluminum Armored MC Cable – 100' per roll EA	EA	1
<b>640-142</b>	14-2 Aluminum Armored MC Cable – 100' per roll EA	EA	1

**Romex Connectors – Metallic**

These Metallic Romex Connectors are made of zinc die cast are cable connectors for Romex wire. U.L. Listed C.S.A. Approved.



CATALOG NO.	DESCRIPTION	UOM	ORDER MULTIPLE
<b>750-RC841</b>	3/8" Romex Connector for 1/2" Knockouts	EA	100
<b>750-RC842</b>	3/4" Romex Connector for 3/4" Knockouts	EA	50

U.L. Listed and C.S.A. Approved.

**BX Set Screw Connectors**

These connectors are for BX cable range of .445 to .630 in diameter. This product is UL listed and CSA approved.



CATALOG NO.	DESCRIPTION	UOM	ORDER MULTIPLE
<b>640-845</b>	Trade Size – 3/8"	EA	100

**Non-Metallic Sheathed Cable (Romex Wire)**

600V building wire. Easy to pull and strip, flame and moisture resistant. Saves time, labor and money. Color coded conductors of copper, PVC insulation and outer jacket with ground. U.L. Listed 719 Federal Specifications J C94.



CATALOG NO.	DESCRIPTION	UOM	ORDER MULTIPLE
<b>620-6-2</b>	6 AWG, 2 Conductors with Ground – 125' per pack	EA	1
<b>620-8-2</b>	8 AWG, 2 Conductors with Ground – 125' per pack	EA	1
<b>620-10-2</b>	10 AWG, 2 Conductors with Ground – 250' per pack	EA	1
<b>620-12-2</b>	12 AWG, 2 Conductors with Ground – 250' per pack	EA	1
<b>620-14-2</b>	14 AWG, 2 Conductors with Ground – 250' per pack	EA	1

U.L. Listed 719 Federal Specifications J-C94.

**EMT (Thinwall) Fittings**


These are used to join EMT conduit to boxes on enclosures.



CATALOG NO.	DESCRIPTION	UOM	ORDER MULTIPLE
<b>625-800</b>	Set Screw Connector – 1/2"	EA	50
<b>625-801</b>	Set Screw Connector – 3/4"	EA	25
<b>625-304</b>	Strap – One Hole – 1/2"	EA	100
<b>625-305</b>	Strap – One Hole – 3/4"	EA	100
<b>625-810</b>	Set Screw Coupling – 1/2"	EA	50
<b>625-811</b>	Set Screw Coupling – 3/4"	EA	25

**Cable Staples**

Cable Staples for NMB Cable (Romex) and Copper Insulated Staples for thermostat wire.



CATALOG NO.	DESCRIPTION	UOM	ORDER MULTIPLE
<b>625-183</b>	Romex Staples – 1/2", pack of 100	PK	1
<b>625-IS5</b>	Copper Insulated #5 Staples for T-Stat Wire	EA	100