

**Inverter Driven Heat Pump**

**24,000 BTU Wall Mount Type**

Job Name \_\_\_\_\_  
 Location \_\_\_\_\_  
 Engineer \_\_\_\_\_  
 Submitted To \_\_\_\_\_  
 Submitted By \_\_\_\_\_  
 Reference \_\_\_\_\_

Date \_\_\_\_\_  
 Approval \_\_\_\_\_  
 Construction \_\_\_\_\_  
 Unit No \_\_\_\_\_  
 Drawing No \_\_\_\_\_

**PRODUCT FEATURES**

- Wireless Remote Controller Included
- Minimum Heat Mode
- Automatic Airflow Adjustment
- Auto/Cool/Dry/Fan/Heat/modes
- Weekly & 24 Hr Timer
- Powerful & Economy Mode
- Auto Changeover
- Cold Air Prevention



**MODEL NUMBERS**

Indoor Unit	ASUH24LPAS
Nominal Capacity	24,000

**LINESET REQUIREMENTS**

Connection Method		Flare
Liquid	in (mm)	Ø1/4 (Ø6.35)
Gas		Ø1/2 (Ø12.7)
Drain hose	Material	PP+HDPE
	in	Ø17/32 (I.D.), Ø5/8 to 21/32 (O.D.)
	mm	Ø13.8 (I.D.), Ø15.8 to 16.7 (O.D.)

**INDOOR DIMENSIONS & WEIGHT**

Net (H x W x D)	in	11 x 38-9/16 x 9-7/16
	mm	280 x 980 x 240
Gross (H x W x D)	in	12-11/16 x 42-7/16 x 13-5/8
	mm	322 x 1,078 x 346
Net Weight	lb (kg)	29 (13)
Gross Weight		37 (17)

**ELECTRICAL SPECIFICATIONS**

Voltage/Frequency/Phase		208/230 V ~ 60 Hz
Voltage Range		187-264 V
Running Current	A	0.46
Input Power	W	55

**SOUND PRESSURE**

Indoor Unit	Cooling	High	dB (A)	49
		Medium		44
		Low		42
		Quiet		31
	Heating	High	dB (A)	47
		Medium		43
		Low		37
		Quiet		32

**FAN DATA**

Airflow Rate	Cooling	High	CFM (m3/h)	642 (1,090)
		Medium		530 (900)
		Low		471 (800)
		Quiet		306 (520)
	Heating	High	CFM (m3/h)	594 (1,010)
		Medium		506 (860)
		Low		377 (640)
		Quiet		306 (520)

**Warranty Information**



7 Year Compressor, 5 Year Parts out-of-the-box Warranty



10 Year Compressor, 10 Year Parts Warranty when registered within 60 days of installation in a residence



12 Year Compressor, 12 Year Parts Warranty when registered within 60 days of installation in a residence, and installed by a Fujitsu Elite contractor

**ENCLOSURE**

Enclosure	Material	Polystyrene
	Color	White

**ACCESSORIES**

UTY-RNRUZ Series	Wired Remote Controller
UTY-RSRY	Simple Remote Controller
UTY-RHRY	Simple Remote Controller
UTY-TWRXZ2*	Communication Kit
UTY-TFSXF1	Wireless LAN Interface
UTY-TTRXZ1	24V Thermostat Interface
UTY-VMSX	MODBUS Converter
FJ-AC-BAC-1L	BACnet Gateway
UTP-MU45A2^	Adapter for ASUH24LPAS
UTY-XWZX	External Connect Kit

\* Required to connect wired remote controller to indoor unit.

^ Required to connect indoor unit to select multi-zone outdoor units.

Reference D&T for specific combinations.




Inverter Driven Heat Pump

24,000 BTU Wall Mount Type

DIMENSIONS

Units: In. (mm)



The Fujitsu logo is a worldwide trademark of Fujitsu General Limited. The Halcyon logo and name is a worldwide trademark of Fujitsu General Limited and is a registered trademark in Japan, the USA and other countries or areas. Copyright 2022 Fujitsu General America, Inc. Fujitsu's products are subject to continuous improvements. Fujitsu reserves the right to modify product design, specifications and information in this brochure without notice and without incurring any obligations.

Note: Specifications are based on the following conditions:  
 Cooling: Indoor temperature of 80°F (26.7°C) DB/67°F (19.4°C) WB, and outdoor temperature of 95°F (35°C) DB/75°F (23.9°C) WB. Heating: Indoor temperature of 70°F (21.1°C) DB/60°F (15.6°C) WB, and outdoor temperature of 47°F (8.3°C) DB/43°F (6.1°C) WB. Pipe length: 25ft. (7.5m), Height difference: 0ft. (0m) (Outdoor unit - indoor unit).