95057WK WIRELESS 5/2, 7 DAY OR NON-PROGRAMMABLE THERMOSTAT KIT



- 5" Backlit Display
- Auto or Manual Changeover
- Residential or Commercial Modes
- Battery Powered with Hardwire Option
- Programmable Fan Control

Specifications	
Dimensions	3.86" x 5.11" x 1.42"
Electrical Information	24 VAC
Control Range	45° to 90°F (7°C to 32°C)

Compatible With
24 VAC Gas, Oil, or Electric Systems
Up to 2H / 2C Conventional Systems, Up to 3H / 2C Heat Pump Systems

ACCESSORIES 6390 INDOOR REMOTE SENSOR



- Simple 2-wire Installation
- For Indoor Use Only
- Mounting Hardware Included
- Accuracy +/- 1°F (+/- .5°C)
- Compatible with CTC® Thermostats: 71100N, 732N, 71157P, 73257P, 84210T

6490 OUTDOOR REMOTE SENSOR



- Simple 2-wire Installation
- For Outdoor Use Only
- Mounting Bracket Included
- Accuracy +/- 1°F (+/- .5°C)
- Compatible with CTC® Thermostats: 71100N, 732N, 71157P, 73257P, 84210T

THERMOSTAT GUARDS





Elite Series

Part No.	Description	Solid Base Dimentions (HxWxD)	Ring Base Dimensions (HxWxD)
Universal			
BTG-UK2	Clear Plastic	8 1/4" x 5 3/8" x 3 1/2"	8 1/8" x 4 5/8" x 3-5/8"
BTG-UM	Metal	8 1/4" x 5 3/8" x 3 1/2"	-
BTG-UWM	Metal	-	6 3/4" x 4 1/2" x 3 9/16"
BTG-UN	Clear Plastic		
Elite			
BTG-EK	Clear Plastic	3 7/8" x 3 1/2" x 2 1/2"	-
Classic			
BTG-K	Clear Plastic	5 1/4" x 4 3/8" x 3"	5 1/4" x 4 5/8" x 3 1/4"
Regal			
BTG-RK	Clear Plastic	6 3/8" x 3 1/2" x 3"	6 3/8" x 3 1/2" x 3 1/4"
BTG-RWM	Metal	-	6 3/8" x 3 1/2" x 3 1/4"
Sentinal			
BTG-54VL	Metal Hinged	6 1/4" x 4 1/4" x 3 1/8"	-
BTG-54VLW	Metal Hinged	-	6" x 3 3/4" x 3 1/8"
Designer			
BTG-DB2	Bronzed Plastic	4 1/4" x 7 5/8" x 2 1/8"	4 1/8" x 7 1/16" x 2 1/4"
F336	Replacement Key	Fits All Models	

18-22 Gauge Steel

Baked Enamel Finish

Louvered Cover

Maximum Protection

Plastic Thermostat Guards Hi-impact Plastic Clear Opaque

All Models	
Locking Key	
Mounting Hardware	
Vertical or Horizontal Mounting	

70