

C4H7T

Up to 17 SEER2 2-Stage Heat Pump with Ion Communicating Control System

2 – 5 Tons
208 / 230 Volt, 1-phase, 60 Hz



SYST0101CW
(Sold separately)



Efficiency/Performance

- Up to 17.0 SEER2
- Up to 13.0 EER2
- Up to 8.1 HSPF2
- Communicating, self-configuring operation when used with Ion System Control
- Outdoor temperature sensor factory installed
- Compressor sound blanket standard
- Isolation compressor grommets
- Sound level as low as 69 dBA

Reliability

- Non-ozone depleting R-410A refrigerant
- Front-seating service valves
- 2-stage scroll compressor
- Internal pressure relief valve
- Internal thermal overload
- Loss of charge switch
- Filter drier
- Balanced refrigeration system for maximum reliability



Use of the AHRI Certified TM Mark indicates a manufacturer's participation in the program. For verification of certification for individual products, go to www.ahridirectory.org.



Durability

- Protection package:
 - Solid, durable sheet metal construction
 - Post-painted cabinet finish over galvanized steel

Limited Warranty*

- 10-year No Hassle Replacement™ limited warranty
- Five-year parts limited warranty
 - With timely registration, an additional five-year parts limited warranty

* For residential applications only. See warranty certificate for complete details and restrictions, including warranty coverage for other applications.

Unit Performance Data

Model Number	Size (tons)	Nominal Btu/hr	Volts-Phase (60 HZ)	Operating Voltage Range	Shipping Dimensions H x W x D (sq) in (mm)	Ship/Operating Weight lbs (kg)
C4H7T24AKAAA	2	24,000	208-230-1	197-253	41-3/4 x 37-13/16 x 37-13/16 (1061.0 x 960.0 x 960.0)	272 / 244 (85.7 / 75.7)
C4H7T36AKAAA	3	36,000			45-3/16 x 37-13/16 x 37-13/16 (1147.4 x 960.0 x 960.0)	290 / 261 (131.5 / 118.4)
C4H7T48AKAAA	4	48,000			52 x 37-13/16 x 37-13/16 (1320.1 x 960.0 x 960.0)	339 / 309 (153.8 / 140.2)
C4H7T60AKAAA	5	60,000			52 x 37-13/16 x 37-13/16 (1320.1 x 960.0 x 960.0)	340 / 310 (154.2 / 140.6)