

Light Commercial Series



CH-09MSPHCT-230VI (INDOOR UNIT)

CEILING CASSETTE

Submittal Data Sheet

Job Name: Location: Engineer: Submitted to: Submitted by: Reference:

Date:	
pproval: onstruction:	
ionstruction:	
Jnit #:	
Orawing #:	



This warranty should be registered on our web-site www.cooperandhunter.us within 60 days of installation. The warranty is only valid when installed by a Licensed HVAC Technician. A warranty period of Seven (7) years on compressor to the original registered end-user. A warranty period of Five (5) years on all parts to the original registered end user. Warranty applies only to products remaining in their original installation location.

GENERAL FEATURES

- Wifi Connector
- Mute Operation
- Silver ion filter
- Anti Cold Air
- Sleep Mode
- Cold Catalyst Filter
- 12 Grades Indoor Fan Speeds
- Self Diagnosis Function

- Two-way Draining Connection
- Golden fin for outdoor and indoor
- Two Direction Airflow
- Double Level Air Flaps
- High Density Filter
- Turbo Operation
- Refrigerant Leakege Detect
- · Emergency Using Function

INDOOR SPECIFICATION

Air flow (Hi/Mi/Lo)	353/306/271 CFM
Sound Preassure level (Hi/Mi/Lo)	37/34.5/32.5 dB(A)
Dimension (W*D*H)	22.44x22.44x10.24 in
Net/Gross weight	31.97/38.14 Lbs

	Cooling		
	Capacity	Btu/h	9000
	SEER		20
	EER	Btu	13
	Heating at 47F		
PERFORMANCE	Capacity	Btu/h	10000
AND	COP	W/W	3.06
EFFICIENCY	HSPF4		10.8
	HSPF5		9.4
	Heating at 17F		
	Rated Capacity	Btu/h	6700

OPERATION TEMPERATURE RANGE

62~86 °F		
cooling	heating	
62∼90 °F	32 ~ 86 °F	

ELECTRICAL

Power supply	V/Hz/Ph	208-230V/ 60Hz/ 1Ph
MCA	A	1.2
MFA	A	15
Fan motor		
Input	W	45
RLA	A	0.9

MCA: Minimum Circuit Ampacity MFA: Max. fuse A RLA: Rated load A

PIPING

Refrigerant piping/Gas side	in	(1/4"/3/8")
Q b .l Q		(





Light Commercial Series

CEILING CASSETTE

CH-09MSPHCT-230VI (INDOOR UNIT)

