

Light Commercial Series



CH-24MSPHCT-230VI (INDOOR UNIT)

CEILING CASSETTE

Submittal Data Sheet

Job Name: Location: Engineer: Submitted to: Submitted by: Reference:

Date:	
pproval: onstruction:	
ionstruction:	
Jnit #:	
Orawing #:	



This warranty should be registered on our web-site www.cooperandhunter.us within 60 days of installation. The warranty is only valid when installed by a Licensed HVAC Technician. A warranty period of Seven (7) years on compressor to the original registered end-user. A warranty period of Five (5) years on all parts to the original registered end user. Warranty applies only to products remaining in their original installation location.

GENERAL FEATURES

- Wifi Connector
- Mute Operation
- Silver ion filter
- Anti Cold Air
- Sleep Mode
- Cold Catalyst Filter
- 12 Grades Indoor Fan Speeds
- Self Diagnosis Function

- Two-way Draining Connection
- Golden fin for outdoor and indoor
- Two Direction Airflow
- Double Level Air Flaps
- High Density Filter
- Turbo Operation
- Refrigerant Leakege Detect
- Emergency Using Function

INDOOR SPECIFICATION

Air flow (Hi/Mi/Lo)	824/735/588 CFM
Sound Preassure level (Hi/Mi/Lo)	49.5/47/44 dB(A)
Dimension (W*D*H)	33.07x33.07x8.07 in
Net/Gross weight	46.3/54.23 Lbs

	Cooling		
	Capacity	Btu/h	24000
	SEER		20
	EER	Btu	11
	Heating at 47F		
PERFORMANCE	Capacity	Btu/h	24000
AND EFFICIENCY	COP	W/W	3.46
	HSPF4		11.5
	HSPF5		10
	Heating at 17F		
	Rated Capacity	Btu/h	16200

OPERATION TEMPERATURE RANGE

62~86 °F		
cooling	heating	
62∼90 °F	32 ~ 86 °F	

ELECTRICAL

Power supply	V/Hz/Ph	208-230V/ 60Hz/ 1Ph	
MCA	A	2.5	
MFA	A	15	
Fan motor			
Input	W	58	
RLA	A	2	

MCA: Minimum Circuit Ampacity MFA: Max. fuse A RLA: Rated load A

PIPING

Refrigerant piping/Gas side	in	(3/8"/5/8")
0 11 0	- 1	` /





Light Commercial Series

CEILING CASSETTE

CH-24MSPHCT-230VI (INDOOR UNIT)



