

CR30K6E-PFV

HCFC, R-22, 60 Hz, 1 - Phase, 208/230 V

Air Conditioning

Production Status: Available for sale to all U.S. customers. Please check with your local Copeland Representative for international availability.

Performance			Mechanical		
Evaporator Temp. (°F)	45.00	45	Displacement (in ³ /Rev):	3.14	
Condensing Temp. (°F)	130.00	100	Displacement (ft ³ /Hr):		
Return Gas Temp. (°F)	65.00	65	Overall Length (in):	10.23	
Liquid Temp. (°F)	115.00	85	Overall Width (in):	9.65	
Capacity (BTU/hr)	27100	37700	Overall Height (in):	13.81	
Power (W):	2570	2120	Mounting Length (in):	7.50	
Current (Amps):	12.25	10.45	Mounting Width (in):	7.50	
EER(BTU/Wh):	10.55	17.8	Mounting Height (in):	14.19	
Mass Flow (lbs/hr):	394	468	Suction Size (in),Type:	3 / 4 Stub	
Sound Data @			Discharge Size (in),Type:	1 / 2 Stub	
Sound Power (dBA):	74 Avg	79 Max	Initial Oil Charge (oz):	45	
Vibration mils(peak-peak):	3.4 Avg	4.4 Max	Oil Recharge (oz):	43	
Record Date:	2020-11-29		Oil Type:	POE	
			Net Weight (lbs):	66.0	
			Internal Free Volume (in ³):		
			Horse Power:		
			*Overall compressor height on Copeland Brand Product's specified mounting grommets.		

Electrical		Capacitors				
		Type	Part No	Low MFD	High MFD	Volts User Description
LRA High* (Amps):	82.0	No data available in table				
LRA Low*(Amps):						
LRA Half Winding (Amps):						
MCC (Amps):	22.4					
Max Operating Current (Amps):						
RLA, MCC/1.4(use for contactor selection)(Amps):	16.0					
RLA, MCC/1.56(use for breaker & wire size selection)(Amps):	14.4					
RPM:	3500					
Box IP :						
UL File No:						
UL File Date:	1984-12-28					

*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.

Alternate Applications

Refrigerant	Voltage	Phase	Frequency	Application
R-404A HFC	200	1	50	High Temp
R-407C HFC	200	1	50	Air Conditioning
R-407C HFC	208/230	1	60	Air Conditioning