

**CR35K6E-TF5**

HCFC, R-22, 60 Hz, 3 - Phase, 200/230 V [. Also Available with Variable Frequency Drives](#)

**Air Conditioning**

**Production Status:** Available for sale to all U.S. customers. Please check with your local Copeland Representative for international availability.

Performance			Mechanical		
Evaporator Temp. (°F)	45.00	45	Displacement (in <sup>3</sup> /Rev):	3.78	
Condensing Temp. (°F)	130.00	100	Displacement (ft <sup>3</sup> /Hr):		
Return Gas Temp. (°F)	65.00	65	Overall Length (in):	10.23	
Liquid Temp. (°F)	115.00	85	Overall Width (in):	9.65	
Capacity (BTU/hr)	34900	46000	Overall Height (in):	14.06	
Power (W):	3160	2530	Mounting Length (in):	7.50	
Current (Amps):	9.6	8.2	Mounting Width (in):	7.50	
EER(BTU/Wh):	11	18.2	Mounting Height (in):	14.44	
Mass Flow (lbs/hr):	510	590	Suction Size (in),Type:	3 / 4 Stub	
Sound Data @			Discharge Size (in),Type:	1 / 2 Stub	
Sound Power (dBA):	75 Avg	80 Max	Initial Oil Charge (oz):	45	
Vibration mils(peak-peak):	3.6 Avg	4.6 Max	Oil Recharge (oz):	43	
Record Date:	2014-03-06		Oil Type:	POE	
			Net Weight (lbs):	65.0	
			Internal Free Volume (in <sup>3</sup> ):		
			Horse Power:		
			*Overall compressor height on Copeland Brand Product's specified mounting grommets.		

Electrical		Capacitors				
LRA High* (Amps):	75.0	Type	Part No	Low MFD	High MFD	Volts User Description
LRA Low*(Amps):		No data available in table				
LRA Half Winding (Amps):						
MCC (Amps):	16					
Max Operating Current (Amps):						
RLA, MCC/1.4(use for contactor selection)(Amps):	11.4					
RLA, MCC/1.56(use for breaker & wire size selection)(Amps):	10.3					
RPM:	3500					
Box IP :						
UL File No:						
UL File Date:	1984-12-28					

\*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.

**Alternate Applications**

<b>Refrigerant</b>	<b>Voltage</b>	<b>Phase</b>	<b>Frequency</b>	<b>Application</b>
R-22 HCFC	200/240	3	50	Air Conditioning
R-407C HFC	200/230	3	60	Air Conditioning
R-407C HFC	200/240	3	50	Air Conditioning