

**CS10K6E-PFV**

HFC, R-134a, 60 Hz, 1 - Phase, 208/230 V

**High Temp**

**Production Status:** Available for sale to all U.S. customers. Please check with your local Copeland Representative for international availability.

Performance			Mechanical		
Evaporator Temp. (°F)	45.00	20	Displacement (in <sup>3</sup> /Rev):	2.26	
Condensing Temp. (°F)	130.00	120	Displacement (ft <sup>3</sup> /Hr):		
Return Gas Temp. (°F)	65.00	65	Overall Length (in):	10.23	
Liquid Temp. (°F)	130.00	120	Overall Width (in):	9.65	
Capacity (BTU/hr)	11600	5840	Overall Height (in):	13.31	
Power (W):	1300	937	Mounting Length (in):	7.50	
Current (Amps):	7.5	6.3	Mounting Width (in):	7.50	
EER(BTU/Wh):	8.9	6.2	Mounting Height (in):	13.69	
Mass Flow (lbs/hr):	202	93	Suction Size (in),Type:	5 / 8 Stub	
Sound Data @			Discharge Size (in),Type:	1 / 2 Stub	
Sound Power (dBA):	0 Avg	0 Max	Initial Oil Charge (oz):	45	
Vibration mils(peak-peak):	0.0 Avg	0.0 Max	Oil Recharge (oz):	43	
Record Date:	1999-07-01		Oil Type:	POE	
			Net Weight (lbs):	62.0	
			Internal Free Volume (in <sup>3</sup> ):		
			Horse Power:		
			*Overall compressor height on Copeland Brand Product's specified mounting grommets.		

Electrical		Capacitors				
		Type	Part No	Low MFD	High MFD	Volts User Description
LRA High* (Amps):	56.0	No data available in table				
LRA Low*(Amps):						
LRA Half Winding (Amps):						
MCC (Amps):	14.2					
Max Operating Current (Amps):	13.80					
RLA, MCC/1.4(use for contactor selection)(Amps):	10.1					
RLA, MCC/1.56(use for breaker & wire size selection)(Amps):	9.1					
RPM:	3500					
Box IP :						
UL File No:	SA-2337					
UL File Date:	1984-12-28					

\*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.

**Alternate Applications**

<b>Refrigerant</b>	<b>Voltage</b>	<b>Phase</b>	<b>Frequency</b>	<b>Application</b>
R-134a HFC	200	1	50	High Temp
R-22 HCFC	208/230	1	60	Medium Temperature
R-404A HFC	200	1	50	Extended Medium Temp
R-404A HFC	208/230	1	60	Extended Medium Temp
R-404A HFC	208/230	1	60	High Temp
R-407A HFC	208/230	1	60	Medium Temperature
R-448A HFO	208/230	1	60	Medium Temperature
R-449A HFO	208/230	1	60	Medium Temperature
R-507 HFC	200	1	50	Extended Medium Temp
R-507 HFC	208/230	1	60	Extended Medium Temp