

## HIGH EFFICIENCY UP TO 19 SEER VARIABLE-SPEED COMMUNICATING AIR CONDITIONER

**2 THRU 5 TONS SPLIT SYSTEM**  
**208 / 230 Volt, 1-phase, 60 Hz**

### REFRIGERATION CIRCUIT

- Variable speed compressor operates at 5 stages with capacity range as wide as 25 - 100%
- High pressure switch
- Suction pressure transducer
- Pressure equalizer valve for easy starting
- Compressor discharge temperature sensor
- Coil temperature sensor
- Copper tube/aluminum fin coil

### PERFORMANCE

- Up to 13.0 EER
- Integrated inverter control enables 5-state operation with a communicating control. Also capable of 2-stage operation with 2-stage thermostat
- Self-configuring installation with the Ion System Control
- Compact ECM fan motor driven by integrated inverter control
- High performance compressor sound shield standard
- Isolation compressor grommets
- Enhanced dehumidification

### EASY TO INSTALL AND SERVICE

- Text based diagnostics with control
- Only 2 control wires required from communicating indoor unit to condenser
- External high and low refrigerant service ports
- Factory charged with R-410A refrigerant
- Adjustments for min and max staging with Ion System Control

### BUILT TO LAST

- High gloss, baked-on powder coat finish over galvanized steel
- Post-painted (black) coil fins
- Coated inlet grille with 3/8" (10mm) spacing for extra protection (hail guard)
- Corner posts for extra strength and style


### WARRANTY\*

- 10 year No Hassle Replacement™ limited warranty
- 5 year parts limited warranty (including compressor and coil)
  - With timely registration, an additional 5 year parts limited warranty (including compressor and coil)

\* For residential applications only. See warranty certificate for complete details and restrictions, including warranty coverage for other applications.



TSTAT0201CW



**smartsense**  
TECHNOLOGY



Qualifying models only

This product has been designed and manufactured to meet ENERGY STAR criteria for energy efficiency when matched with appropriate coil components. However, proper refrigerant charge and proper air flow are critical to achieve rated capacity and efficiency. Installation of this product should follow the manufacturer's refrigerant charging and air flow instructions. Failure to confirm proper charge and airflow may reduce energy efficiency and shorten equipment life.



Use of the AHRi Certified™ Mark indicates a manufacturer's participation in the program. For verification of certification for individual products, go to [www.ahrirectory.org](http://www.ahrirectory.org).

UNIT PERFORMANCE DATA							
Model Number	Size (tons)	Nominal Btu/hr	Min. Circuit Ampacity	Max. Fuse or Breaker	Operating Dimensions height x length/width(sq.) in. (mm)	Ship / Operating Weight lbs. (kg)	Notes
CVA924GKA	2	24,000	13.5	20	31-13/16 x 23-1/8 (807 x 587)	128/150(58/68)	
CVA925GKA‡	2	24,000	23.6	40	38-1/2 x 23-1/8 (980 x 587)	152/177 (69/80)	
CVA936GKA	3	36,000	24.2	40		152/177 (69/80)	
CVA937GKA‡	3	36,000	26.0	40	38-15/16 x 31-3/16 (989 x 792)	205/242 (93/110)	
CVA948GKA	4	48,000	27.3	40		205/242 (93/110)	
CVA949GKA‡	4	48,000	26.0	40	43-11/16 x 35 (1111 x 889)	249/285 (113/129)	
CVA960GKA	5	60,000	40.0	60	42-5/16 x 31-3/16 (1075 x 792)	229/268(104/121)	

‡ = Meets Energy Star criteria when matched with appropriate coil