



600A True-RMS Dual Display Clamp Meter w/ DC Amps & Differential Temperature



Functions

- 600A AC/DC
- 1000V DC
- 750V AC
- 2000 μ A AC/DC
- 60M Ω Resistance
- Capacitance: 2000 μ F
- Differential Temperature: -328° to 2462°F
- Frequency/Duty Cycle
- Audible Continuity
- Diode Test
- Non-Contact Voltage Detection
- LRA Inrush
- Low Z (impedance)

Features

- TRMS
- Backlit Dual Display and Worklight
- Min/Max/Avg/Hold
- Peak Hold
- Auto Volts & Amp selection
- Built-in Magnet w/ hanging strap
- Test Lead Storage
- Visible high-voltage alert
- Easy access battery cover latches
- Overmolded grip
- Auto and Manual ranging
- Input Jack Lock
- Auto calibration
- Auto Power Off
- Low Battery Indicator
- 2-Year limited warranty

Application

- Circuits in molex plugs, and diode malfunctions. Measure capacitance, voltage, microamps, circuit continuity, resistance, and temperature via K-Type thermocouples
- Flame sensing
- Check system boards and live wires

Includes

- Silicone Test Leads (ATL58)
- Back Probes (APB3)
- Alligator Clips (AAC3)
- Temperature Probes 2 (ATT29)
- Soft Case (AC560)
- Batteries 4 (AAA)
- Manual



DESIGNED BY
MADE BY
UEI

Safety Rated: CATIV 600V / CATIII 1000V
Certified to IEC 61010-1, 3rd edition



Specifications

AC Amps Measurement - Jaw Input

Range	Resolution	Accuracy	Overload Protection
60.00A	0.01A	±2.0% +8dgts	600V RMS
600.0A	0.1A	±2.0% +8dgts	

45 to 400Hz TRMS
Minimum Current for Clamp Measurement 0.3A

DC Amps Measurement - Jaw Input

Range	Resolution	Accuracy	Overload Protection
60.00A	0.01A	±2.0% +8dgts	600V RMS
600.0A	0.1A	±2.0% +8dgts	

Minimum Current for Clamp Measurement 0.2A

AC Microamps Measurement- Test Lead input

Range	Resolution	Accuracy	Overload Protection
600µA	0.1µA	±1.5% +3 dgts	600V RMS
2000µA	1µA		

45 to 400Hz TRMS

DC Microamps Measurement- Test Lead input

Range	Resolution	Accuracy	Overload Protection
600µA	0.1µA	±1.5% +2 dgts	600V RMS
2000µA	1µA		

AC Volts Measurement

Range	Resolution	Accuracy	Overload Protection
600.0mV	0.1mV	±1.0% +3 dgts	1000V RMS
6.000V	0.001V		
60.00V	0.01V		
600.0V	0.1V		
750V	1V		

45 to 400Hz TRMS

DC Volts Measurement

Range	Resolution	Accuracy	Overload Protection
600.0mV	0.1mV	±0.5% +4 dgts	1000V RMS
6.000V	0.001V		
60.00V	0.01V		
600.0V	0.1V		
1000V	1V	±0.8% +5 dgts	

Ohms Measurement

Range	Resolution	Accuracy	Overload Protection
600.0Ω	0.1Ω	±0.8 +3 dgts	600V RMS
6.000kΩ	0.001kΩ		
60.00kΩ	0.01kΩ		
600.0kΩ	0.1kΩ		
6.000MΩ	0.001MΩ		
60.00MΩ	0.01MΩ	±1.2% +3 dgts	

Capacitance Measurement

Range	Resolution	Accuracy	Overload Protection
10.00nF	0.01nF	3.0% +5 dgts	600V RMS
100.0nF	0.1nF		
1.000µF	0.001µF		
10.00µF	0.01µF		
100.0µF	0.1µF		
2000µF	1µF		

WARNING to avoid damaging the meter or equipment under test, safely discharge Capacitors before measuring capacitance. Large value capacitors should be discharged through appropriate resistance load. Use the DC Voltage to confirm capacitor discharge.

Diode Test Measurement

Range	Resolution	Accuracy	Overload Protection
3.0V	<3.2V DC	0.25mA	600V RMS

Temperature Measurement

Range	Resolution	Accuracy	Overload Protection
-328° to 999°F (-200° to 999°C)	0.1°F (0.1°C)	±1.0% +3.6°F (±1.0% +2.0°C)	30V RMS
1000° to 2462°F (1000° to 1350°C)	1°F (1°C)	±1.0% +3°F (±1.0% +2°C)	

Frequency Measurement - Test lead input

Range	Resolution	Accuracy	Overload Protection
99.99Hz	0.01Hz	±0.1% +3 dgts	1000V RMS
999.9Hz	0.1Hz		
9.999kHz	0.001kHz		
99.99kHz	0.01kHz		

Duty Cycle

Range	Accuracy	Overload Protection
1.0to 99.0%	±(0.2% per kHz +0.1% +5 dgts)	1000V RMS

Audible Continuity Measurement

Open Circuit Voltage <1.0V	Overload Protection
Threshold <40Ω	600V RMS

Safety Rated: CATIV 600V / CATIII 1000V
Certified to IEC 61010-1, 3rd edition

Downloads



Manual



Data Sheet

