


Domestic Hot Water Tanks
Corrosion-resistant stainless steel, 42-119 USG



VITOCELL 300



VITOCCELL 300

Experience Viessmann hot water technology. Comfort, convenience, and reliability in one package. Available in vertical and horizontal designs, from 42 to 119 USG. See how you can improve your domestic hot water comfort today.



Vitocell 300-W, EVIA
Smaller size and color to match wall-mounted boilers.



Vitocell 300-V
Convenient, durable, hygienic.



Vitocell 300-H
Compact and stackable.

Benefits at a glance:

- No worries — Lifetime warranty for original owner on all Vitocell 300 DHW Tanks.
- Convenience — Fast recovery rates ensure abundant supply of domestic hot water all day long.
- Comfort — Tank coil extends to tank bottom guaranteeing even water temperatures at all times.
- High level of operational reliability and a long service life due to high alloy stainless steel construction.
- High-performance insulation keeps standby losses and operating cost at a minimum.
- All sizes now with NPT connections.
- Extremely efficient indirect hot water production by the boiler. Save up to 50% of your operating cost compared to conventional direct-fired hot water production.
- Space-saving options: Vitocell 300-H tanks can be stacked on top of each other (92 and 119 USG sizes). Zero clearance to combustibles for all Vitocell 300 tanks.
- Scale- and corrosion-resistant, ideal for areas with poor water quality. Completely hygienic.
- High-volume hot water – Several Vitocell 300 tanks can be combined into tank batteries.

Model		-W (vertical)			-V (vertical)			-H (horizontal)				-B (dual-coil vertical)	
Capacity	USG	42	53	79	119*	42	53	92	119	79	119*		
	liters	160	200	300	450	160	200	350	450	300	450		
Dimensions (inches)	Width	23 ^{3/4}	22 ^{7/8}	27 ^{3/4}	36 ^{3/8}	25 ^{1/4}	25 ^{1/4}	32 ^{3/4}	35 ^{3/4}	27 ^{3/4}	38 ^{3/8}		
	Depth	23	25 ^{1/2}	25	38 ^{3/8}	42 ^{1/4}	48 ^{1/4}	62 ^{1/2}	65	25	36 ^{3/8}		
	Height	47	56	70	69 ^{1/2}	25 ^{3/4}	25 ^{3/4}	31	35	70	69 ^{1/2}		
Weight	lbs.	141	167	220	244	168	185	379	421	251	276		

*Removable soft foam wrap around insulation.

