

Sid Harvey part #'s F3-61A, F3-62A & F3-63A

SDS # Z0452

SAFETY DATA SHEET

SDS 0011

Section 1 -- PRODUCT AND COMPANY IDENTIFICATION

| | | |
|--|---------------------------------|---|
| | HMIS CODES | |
| PRODUCT NAME | Health | 1 |
| RectorSeal No. 5 | Flammability | 2 |
| | Reactivity | 0 |
| PRODUCT CODES | PPI | B |
| 25112, 25191, 25271, 25300, 25431, 25551, 25552, 25631, 25633, 25780, 25790, 25793 | | |
| CHEMICAL FAMILY | | |
| Organic | | |
| USE | | |
| Pipe Thread Sealant | | |
| MANUFACTURER'S NAME | EMERGENCY TELEPHONE NO. | |
| The RectorSeal Corporation | Chemtrec 24 Hours | |
| 2601 Spenwick Drive | (800)424-9300 USA | |
| Houston, Texas 77055 USA | (703)527-3887 International | |
| DATE OF VALIDATION | TECHNICAL SERVICE TELEPHONE NO. | |
| January 23, 2015 | (800)231-3345 or (713)263-8001 | |
| DATE OF PREPARATION | | |
| January 9, 2013 | | |

Section 2 -- HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

OSHA Hazards

Combustable

TARGET ORGANS

Not Classified

GHS CLASSIFICATION

PHYSICAL HAZARDS

Combustable liquid (Category 4)

HEALTH HAZARDS

Acute Toxicity:

Oral: Not Classified

Dermal: Not Classified

Inhalation: Not Classified

Skin Corrosion/Irritation: Not Classified

Serious Eye Damage/Eye Irritation: Not Classified

Skin Sensitization: Not Classified

Respiratory Sensitization: Not Classified

Germ Cell Mutagenicity: Not Classified

Carcinogenicity: See Section 11

Reproductive Toxicology: Not Classified

Target Organ Systemic Toxicity - Single Exposure: Not Classified

Target Organ Systemic Toxicity - Repeated Exposure: Not Classified

Aspiration Toxicity: Not Classified

GHS Label elements, including precautionary statements

Pictogram: Harmful / Irritant

Signal Word: Warning

Hazard Statements

H303 - May be harmful if swallowed.

H313 - May be harmful in contact with skin.

H335 + H336 - May cause respiratory irritation, and drowsiness or dizziness.

Precautionary Statements

P102 - Keep out of reach of children.

P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking

P240 - Ground/Bond container and receiving equipment

P261 - Avoid breathing dust/fume/gas/mist/vapors/spray
 P262 - Do not get in eyes, on skin, or on clothing.
 P264 - Wash hands thoroughly after handling.
 P280 - Wear protective gloves/protective clothing/eye protection/face protection.
 P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
 P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes.
 Remove contact lenses, if present and easy to do. Continue rinsing.
 P362 - Take off contaminated clothing and wash before reuse.
 EUH066 - Repeated exposure may cause skin dryness or cracking
 Precautionary Statements - EU No. 1272/2008

 SUMMARY OF ACUTE HAZARDS

Irritation to eyes, nose and throat; drowsiness, narcosis, tremors and other CNS effects at high concentration.

ROUTE OF EXPOSURE, SIGNS AND SYMPTOMS

INHALATION

Nasal and respiratory irritation, dizziness, narcosis, headache, nausea, CNS depression and unconsciousness.

EYE CONTACT

Watering, blurred vision, inflammation and irritation which can result in corneal injury.

SKIN CONTACT

Irritation, dermatitis.

INGESTION

Nausea, vomiting; CNS depression; irritation of gastrointestinal tract, liver and peritoneal wall; lung congestion.

SUMMARY OF CHRONIC HAZARDS

Skin irritation and dermatitis. Possible liver and kidney damage.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

Individuals with pre-existing or chronic diseases of the eyes, skin, respiratory system, cardiovascular system, gastrointestinal system, liver or kidneys may have increased susceptibility to excessive exposures.

 Section 3 -- COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENT: Diacetone Alcohol

PERCENTAGE BY WEIGHT: 20-30

CAS NUMBER: 123-42-2

EC# : 204-626-7

Section 4 -- FIRST AID MEASURES

If INHALED: If overcome by exposure, remove victim to fresh air immediately. Give oxygen or artificial respiration as needed. Obtain emergency medical attention. Prompt action is essential.
 If on SKIN: Wash with soap and water. If irritation occurs, seek medical attention.
 If in EYES: Flush eyes with large amounts of water for 15 minutes. Get medical attention.
 If SWALLOWED: If swallowed, call a physician immediately. Only induce vomiting at the instruction of a physician. Never give anything by mouth to an unconscious person.

 Section 5 -- FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

Foam, dry chemical, carbon dioxide or water fog.

SPECIAL FIRE FIGHTING PROCEDURES: Wear self-contained breathing apparatus (SCBA) and other protective clothing. Hazardous decomposition products possible (see Section 10).

UNUSUAL FIRE AND EXPLOSION HAZARDS: Combustible - moderate flash point.

Vapors heavier than air and may travel along the ground or to low spots at considerable distances to a source of ignition resulting in potential flashback. Burning liquid may float on water. Heat may build up

pressure and rupture containers.

=====
 Section 6 -- ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Remove all sources of ignition. Use absorbent materials to prevent footing hazard and to contain. Ventilate area with natural or explosion-proof, forced air ventilation. Avoid flushing into sewers, drains, waterways, and soil. Wear protective clothing and respiratory protection during cleanup.

=====
 Section 7 -- HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Keep container closed and upright when not in use. Do not store near heat, sparks, or open flames. OTHER PRECAUTIONS: Avoid prolonged or repeated contact with skin or clothing. Empty containers may contain residues; treat as if full and observe all products precautions. Do not reuse empty containers. KEEP OUT OF REACH OF CHILDREN.

=====
 Section 8 -- EXPOSURE CONTROLS/PERSONAL PROTECTION

| INGREDIENT | UNITS |
|-------------------|--------|
| Diacetone Alcohol | |
| ACGIH TLV | 50 ppm |
| OSHA PEL | 50 ppm |

RESPIRATORY PROTECTION (SPECIFY TYPE): In confined poorly ventilated areas, use NIOSH/MSHA approved air purifying or supplied air purifying or supplied air respirators.

VENTILATION - LOCAL EXHAUST: Acceptable

SPECIAL: Explosion-proof equipment.

MECHANICAL (GENERAL): Preferable

OTHER: N/A

PROTECTIVE GLOVES: Wear rubber gloves.

EYE PROTECTION: Chemical splash goggles (ANSI Z-87.1 or equivalent)

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Coveralls recommended.

WORK/HYGIENIC PRACTICES: Where use can result in skin contact, wash exposed areas thoroughly before eating, drinking, smoking, or leaving work area. Launder contaminated clothing before reuse.

=====
 Section 9 -- PHYSICAL AND CHEMICAL PROPERTIES

| | |
|---|--------------------------|
| BOILING POINT: | 322 F (161 C) @ 760mm Hg |
| SPECIFIC GRAVITY (H2O = 1): | 1.38 |
| VAPOR PRESSURE (mm Hg): | 0.3 @ 68 F (20 C) |
| MELTING POINT: | N/A |
| VAPOR DENSITY (AIR = 1): | 1.1 |
| EVAPORATION RATE (ETHYL ACETATE = 1): | 0.14 |
| APPEARANCE/ODOR: | Yellow Paste/Mild Odor |
| SOLUBILITY IN WATER: | 23% |
| VOLATILE ORGANIC COMPOUNDS(VOC)Content (Theoretical Percentage By Weight): | 23% or (317 g/L) |
| Flash POINT | 150 F (65 C) SETA CC |
| LOWER EXPLOSION LIMIT | N/D |
| UPPER EXPLOSION LIMIT | N/D |

=====
 Section 10 -- STABILITY AND REACTIVITY

STABILITY: Stable

CONDITIONS TO AVOID: Heat, sparks, open flames, and strong oxidizing. Temperatures above 500 F (260 C).

INCOMPATIBILITY (MATERIALS TO AVOID): Gaseous oxygen, strong oxidizing materials, molten alkali metals.

HAZARDOUS DECOMPOSITION PRODUCTS: CO, CO2 and fragmented hydrocarbons.

HAZARDOUS POLYMERIZATION: Will not occur.

=====
Section 11 -- TOXICOLOGY INFORMATION
=====

CHRONIC HEALTH HAZARDS

No ingredients in this product is an IARC, NTP or OSHA Lister carcinogen.

TOXICOLOGY DATA

Ingredient Name

Diacetone Alcohol

Oral-Rat LD50:4000 mg/kg
Inhalation-Human TCLO: 100 ppm

=====
Section 12 -- Ecological Information
=====

ECOLOGICAL DATA

Ingredient Name

Diacetone Alcohol

Food Chain Concentration Potential N/A
WATERFOWL TOXICITY N/A
BOD N/A
AQUATIC TOXICITY N/A

=====
Section 13 -- DISPOSAL CONSIDERATIONS
=====

Waste Classification: Non-regulated solid waste
Disposal Method: Approved landfill
Waste from this product is not considered hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Dispose of in accordance with Federal, State, and Local regulation regarding pollution.

=====
Section 14 -- TRANSPORTATION INFORMATION
=====

DOT: Non-Regulated
OCEAN (IMDG): Non-Regulated
AIR (IATA): Non-Regulated
WHMIS (CANADA): Non-Regulated

=====
Section 15 -- REGULATORY INFORMATION
=====

REGULATORY DATA

Ingredient Name

Diacetone Alcohol

SARA 313 N/A
TSCA Inventory Yes
CERCLA RQ N/A
RCRA Code N/A

=====
Section 16 -- OTHER INFORMATION
=====

This document is prepared pursuant to the OSHA Hazard Communication Standard (29 CFR 1910.1200). The information herein is given in good faith, but no warranty, expressed or implied is made. Consult RectorSeal for further information: (713) 263-8001

MATERIAL SAFETY DATA SHEET

MSDS 0011

Section 1 -- PRODUCT AND COMPANY IDENTIFICATION

| | | | |
|---------------------|---|---------------------------------|---|
| PRODUCT NAME | RectorSeal No. 5 | HMS CODES | Health 1 Flammability 2 Reactivity 0 PPI B |
| PRODUCT CODES | 25631, 25551, 25431, 25300, 25271, 25191, 25112, 25780, 25790 | | |
| CHEMICAL FAMILY: | Organic | | |
| USE | Pipe Thread Sealant | | |
| MANUFACTURER'S NAME | The RectorSeal Corporation 2601 Spenwick Drive Houston, Texas 77055 USA | EMERGENCY TELEPHONE NO. | Chemtrec 24 Hours (800) 424-9300 |
| VALIDATION DATE | February 10, 2006 | TECHNICAL SERVICE TELEPHONE NO. | (800) 231-3345 |
| REVISION DATE | February 10, 2006 | | |

Section 2 -- COMPOSITION/INFORMATION ON INGREDIENTS

| % by WT | CAS No. | INGREDIENT | UNITS |
|---------|----------|-------------------|--------|
| 20-30 | 123-42-2 | Diacetone Alcohol | |
| | | ACGIH TLV | 50 ppm |
| | | OSHA PEL | 50 ppm |

Section 3 -- HAZARDS IDENTIFICATION

SUMMARY OF ACUTE HAZARDS

Irritation to eyes, nose and throat; drowsiness, narcosis, tremors and other CNS effects at high concentration.

ROUTE OF EXPOSURE, SIGNS AND SYMPTOMS

INHALATION

Nasal and respiratory irritation, dizziness, narcosis, headache, nausea, CNS depression and unconsciousness.

EYE CONTACT

Watering, blurred vision, inflammation and irritation which can result in corneal injury.

SKIN CONTACT

Irritation, dermatitis.

INGESTION

Nausea, vomiting; CNS depression; irritation of gastrointestinal tract, liver and peritoneal wall; lung congestion.

SUMMARY OF CHRONIC HAZARDS

Skin irritation and dermatitis. Possible liver and kidney damage.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

Individuals with pre-existing or chronic diseases of the eyes, skin, respiratory system, cardiovascular system, gastrointestinal system, liver or kidneys may have increased susceptibility to excessive exposures.

Section 4 -- FIRST AID MEASURES

| | |
|---------------|---|
| If INHALED: | If overcome by exposure, remove victim to fresh air immediately. Give oxygen or artificial respiration as needed. Obtain emergency medical attention. Prompt action is essential. |
| If on SKIN: | Wash with soap and water. If irritation occurs, seek medical attention. |
| If in EYES: | Flush eyes with large amounts of water for 15 minutes. Get medical attention. |
| If SWALLOWED: | If swallowed, call a physician immediately. Only induce vomiting at the instruction of a physician. Never give anything by mouth to an unconscious person. |

Section 5 -- FIRE FIGHTING MEASURES

| | | |
|----------------------|-----|-----|
| FLASH POINT | LEL | UEL |
| 150 F (65 C) SETA CC | N/D | N/D |

EXTINGUISHING MEDIA

Foam, dry chemical, carbon dioxide or water fog.

SPECIAL FIRE FIGHTING PROCEDURES: Wear self-contained breathing apparatus (SCBA) and other protective clothing. Hazardous decomposition products possible (see Section 10).

UNUSUAL FIRE AND EXPLOSION HAZARDS: Combustible - moderate flash point. Vapors heavier than air and may travel along the ground or to low spots at considerable distances to a source of ignition resulting in potential flashback. Burning liquid may float on water. Heat may build up pressure and rupture containers.

 Section 6 -- ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Remove all sources of ignition. Use absorbent materials to prevent footing hazard and to contain. Ventilate area with natural or explosion-proof, forced air ventilation. Avoid flushing into sewers, drains, waterways, and soil. Wear protective clothing and respiratory protection during cleanup.

 Section 7 -- HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Keep container closed and upright when not in use. Do not store near heat, sparks, or open flames. OTHER PRECAUTIONS: Avoid prolonged or repeated contact with skin or clothing. Empty containers may contain residues; treat as if full and observe all products precautions. Do not reuse empty containers. KEEP OUT OF REACH OF CHILDREN.

 Section 8 -- EXPOSURE CONTROLS/PERSONAL PROTECTION

RESPIRATORY PROTECTION (SPECIFY TYPE): In confined poorly ventilated areas, use NIOSH/MSHA approved air purifying or supplied air purifying or supplied air respirators.
 VENTILATION - LOCAL EXHAUST: Acceptable
 SPECIAL: Explosion-proof equipment.
 MECHANICAL (GENERAL): Preferable
 OTHER: N/A
 PROTECTIVE GLOVES: Wear rubber gloves.
 EYE PROTECTION: Chemical splash goggles (ANSI Z-87.1 or equivalent)
 OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Coveralls recommended.
 WORK/HYGIENIC PRACTICES: Where use can result in skin contact, wash exposed areas thoroughly before eating, drinking, smoking, or leaving work area. Launder contaminated clothing before reuse.

 Section 9 -- PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT: 322 F (161 C) @ 760mm Hg
 SPECIFIC GRAVITY (H2O = 1): 1.38
 VAPOR PRESSURE (mm Hg): 0.3 @ 68 F (20 C)
 MELTING POINT: N/A
 VAPOR DENSITY (AIR = 1): 1.1
 EVAPORATION RATE (ETHYL ACETATE = 1): 0.14
 APPEARANCE/ODOR: Yellow Paste/Mild Odor
 SOLUBILITY IN WATER: 23%

VOLATILE ORGANIC COMPOUNDS(VOC)Content
 (Theoretical Percentage By Weight): 23% or (230 g/L)

 Section 10 -- STABILITY AND REACTIVITY

STABILITY: Stable
 CONDITIONS TO AVOID: Heat, sparks, open flames, and strong oxidizing. Temperatures above 500 F (260 C).
 INCOMPATIBILITY (MATERIALS TO AVOID): Gaseous oxygen, strong oxidizing materials, molten alkali metals.
 HAZARDOUS DECOMPOSITION PRODUCTS: CO, CO2 and fragmented hydrocarbons.
 HAZARDOUS POLYMERIZATION: Will not occur.

 Section 11 -- TOXICOLOGY INFORMATION

CHRONIC HEALTH HAZARDS
 No ingredients in this product is an IARC, NTP or OSHA Listed carcinogen.

 TOXICOLOGY DATA
 Ingredient Name

Di acetone Alcohol
 Oral-Rat LD50: 4000 mg/kg
 Inhalation-Human TCLo: 100 ppm

 Section 12 -- Ecological Information

 ECOLOGICAL DATA
 Ingredient Name

 Di acetone Alcohol
 Food Chain Concentration Potential N/A
 WATERFOWL TOXICITY N/A
 BOD N/A
 AQUATIC TOXICITY N/A
 =====

Section 13 -- DISPOSAL CONSIDERATIONS

 Waste Classification: Non-regulated solid waste
 Disposal Method: Approved Landfill
 Waste from this product is not considered hazardous as defined under the
 Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Dispose of in
 accordance with Federal, State, and Local regulation regarding pollution.
 =====

Section 14 -- TRANSPORTATION INFORMATION

 DOT: Non-Regulated
 OCEAN (IMDG): Non-Regulated
 AIR (IATA): Non-Regulated
 WHMIS (CANADA): Non-Regulated
 =====

Section 15 -- REGULATORY INFORMATION

 REGULATORY DATA
 Ingredient Name

 Di acetone Alcohol
 SARA 313 N/A
 TSCA Inventory Yes
 CERCLA RQ N/A
 RCRA Code N/A
 =====

Section 16 -- OTHER INFORMATION

 This document is prepared pursuant to the OSHA Hazard Communication
 Standard (29 CFR 1910.1200). The information herein is given in good faith,
 but no warranty, expressed or implied is made. Consult RectorSeal for further
 information: (713) 263-8001

~~MSDS Number – Z0343~~

Sid Harvey Item number – F3-62A

MATERIAL SAFETY DATA SHEET

MSDS 0011

Section 1 -- PRODUCT AND COMPANY

IDENTIFICATION

| | HMIS CODES | |
|---|--------------|---|
| PRODUCT NAME | Health | 1 |
| RectorSeal No. 5 | Flammability | 2 |
| | Reactivity | 0 |
| PRODUCT CODES | PPI | B |
| 25631, 25551, 25431, 25300, 25271, 25191, 25112, 25780, 25790 | | |

CHEMICAL FAMILY:

Organic

USE

Pipe Thread Sealant

MANUFACTURER'S NAME

The RectorSeal Corporation
2601 Spenwick Drive
Houston, Texas 77055 USA

EMERGENCY TELEPHONE NO.

Chemtrec 24 Hours
(800) 424-9300

VALIDATION DATE

February 10, 2006

TECHNICAL SERVICE TELEPHONE NO.

(800) 231-3345

REVISION DATE

February 10, 2006

Section 2 -- COMPOSITION/INFORMATION ON INGREDIENTS

| % by WT | CAS No. | INGREDIENT | UNITS |
|---------|----------|-------------------|--------|
| 20-30 | 123-42-2 | Diacetone Alcohol | |
| | | ACGIH TLV | 50 ppm |
| | | OSHA PEL | 50 ppm |

Section 3 -- HAZARDS IDENTIFICATION

SUMMARY OF ACUTE HAZARDS

Irritation to eyes, nose and throat; drowsiness, narcosis, tremors and other CNS effects at high concentration.

ROUTE OF EXPOSURE, SIGNS AND SYMPTOMS

INHALATION

Nasal and respiratory irritation, dizziness, narcosis, headache, nausea, CNS depression and unconsciousness.

EYE CONTACT

Watering, blurred vision, inflammation and irritation which can result in corneal injury.

SKIN CONTACT

Irritation, dermatitis.

INGESTION

Nausea, vomiting; CNS depression; irritation of gastrointestinal tract, liver and peritoneal wall; lung congestion.

SUMMARY OF CHRONIC HAZARDS

Skin irritation and dermatitis. Possible liver and kidney damage.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

Individuals with pre-existing or chronic diseases of the eyes, skin, respiratory system, cardiovascular system, gastrointestinal system, liver or kidneys may have increased susceptibility to excessive exposures.

=====
Section 4 -- FIRST AID MEASURES

If INHALED: If overcome by exposure, remove victim to fresh air immediately. Give oxygen or artificial respiration as needed. Obtain emergency medical attention. Prompt action is essential.

If on SKIN: Wash with soap and water. If irritation occurs, seek medical attention.

If in EYES: Flush eyes with large amounts of water for 15 minutes. Get medical attention.

If SWALLOWED: If swallowed, call a physician immediately. Only induce vomiting at the instruction of a physician. Never give anything by mouth to an unconscious person.

=====
Section 5 -- FIRE FIGHTING MEASURES

| | | |
|----------------------|-----|-----|
| FLASH POINT | LEL | UEL |
| 150 F (65 C) SETA CC | N/D | N/D |

EXTINGUISHING MEDIA

Foam, dry chemical, carbon dioxide or water fog.

SPECIAL FIRE FIGHTING PROCEDURES: Wear self-contained breathing apparatus (SCBA) and other protective clothing. Hazardous decomposition products possible (see Section 10).

UNUSUAL FIRE AND EXPLOSION HAZARDS: Combustible - moderate flash point. Vapors heavier than air and may travel along the ground or to low spots at considerable distances to a source of ignition resulting in potential flashback. Burning liquid may float on water. Heat may build up pressure and rupture containers.

=====
Section 6 -- ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Remove all sources of ignition. Use absorbent materials to prevent footing hazard and to contain. Ventilate area with natural or explosion-proof, forced air ventilation. Avoid flushing into sewers, drains, waterways, and

soil.

Wear protective clothing and respiratory protection during cleanup.

=====
Section 7 -- HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Keep container closed and upright when not in use. Do not store near heat, sparks, or open flames.
OTHER PRECAUTIONS: Avoid prolonged or repeated contact with skin or clothing. Empty containers may contain residues; treat as if full and observe all products precautions. Do not reuse empty containers.
KEEP OUT OF REACH OF CHILDREN.

=====
Section 8 -- EXPOSURE CONTROLS/PERSONAL PROTECTION

RESPIRATORY PROTECTION (SPECIFY TYPE): In confined poorly ventilated areas, use NIOSH/MSHA approved air purifying or supplied air purifying or supplied air respirators.
VENTILATION - LOCAL EXHAUST: Acceptable
SPECIAL: Explosion-proof equipment.
MECHANICAL (GENERAL): Preferable
OTHER: N/A
PROTECTIVE GLOVES: Wear rubber gloves.
EYE PROTECTION: Chemical splash goggles (ANSI Z-87.1 or equivalent)
OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Coveralls recommended.
WORK/HYGIENIC PRACTICES: Where use can result in skin contact, wash exposed areas thoroughly before eating, drinking, smoking, or leaving work area. Launder contaminated clothing before reuse.

=====
Section 9 -- PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT: 322 F (161 C) @ 760mm Hg
SPECIFIC GRAVITY (H2O = 1): 1.38
VAPOR PRESSURE (mm Hg): 0.3 @ 68 F (20 C)
MELTING POINT: N/A
VAPOR DENSITY (AIR = 1): 1.1
EVAPORATION RATE (ETHYL ACETATE = 1): 0.14
APPEARANCE/ODOR: Yellow Paste/Mild Odor
SOLUBILITY IN WATER: 23%

VOLATILE ORGANIC COMPOUNDS(VOC)Content
(Theoretical Percentage By Weight): 23% or (230 g/L)

=====
Section 10 -- STABILITY AND REACTIVITY

STABILITY: Stable
CONDITIONS TO AVOID: Heat, sparks, open flames, and strong oxidizing.
Temperatures above 500 F (260 C).

INCOMPATIBILITY (MATERIALS TO AVOID): Gaseous oxygen, strong oxidizing materials, molten alkali metals.

HAZARDOUS DECOMPOSITION PRODUCTS: CO, CO2 and fragmented hydrocarbons.

HAZARDOUS POLYMERIZATION: Will not occur.

=====
Section 11 -- TOXICOLOGY INFORMATION

CHRONIC HEALTH HAZARDS

No ingredients in this product is an IARC, NTP or OSHA Lister carcinogen.

TOXICOLOGY DATA

Ingredient Name

Diacetone Alcohol

Oral-Rat LD50:4000 mg/kg
Inhalation-Human TCLo: 100 ppm

=====
Section 12 -- Ecological Information

ECOLOGICAL DATA

Ingredient Name

Diacetone Alcohol

Food Chain Concentration Potential N/A
WATERFOWL TOXICITY N/A
BOD N/A
AQUATIC TOXICITY N/A

=====
Section 13 -- DISPOSAL CONSIDERATIONS

Waste Classification: Non-regulated solid waste

Disposal Method: Approved landfill

Waste from this product is not considered hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Dispose of in accordance with Federal, State, and Local regulation regarding pollution.

=====
Section 14 -- TRANSPORTATION INFORMATION

DOT: Non-Regulated
OCEAN (IMDG): Non-Regulated
AIR (IATA): Non-Regulated
WHMIS (CANADA): Non-Regulated

=====
Section 15 -- REGULATORY INFORMATION

REGULATORY DATA

Ingredient Name

Diacetone Alcohol

| | |
|----------------|-----|
| SARA 313 | N/A |
| TSCA Inventory | Yes |
| CERCLA RQ | N/A |
| RCRA Code | N/A |

=====
Section 16 -- OTHER INFORMATION

This document is prepared pursuant to the OSHA Hazard Communication Standard (29 CFR 1910.1200). The information herein is given in good faith, but no warranty, expressed or implied is made. Consult RectorSeal for further

information: (713) 263-8001