

5-5/8" DIAMETER MOTORS

A.O. Smith

Masterfit Multiple HP Replacement Motors

Permanent Split Capacitor. Direct Drive Fan and Blower Motor.



FEATURES:

- 40°C ambient.
- Open enclosure.
- 1/2" x 5" flatted shaft.
- Reversing plug.
- Resilient rings.
- Extended thru bolts.
- 26" leads.
- Automatic protector.



HP	Amps	RPM	Speeds	370V Capacitor	Bearing Type	Item
1/2	3.9 @ 208-230V	1075	All	10	Sleeve	FD6000
1/3	3.6 @ 208-230V		All	5 or 7.5		
1/4	2.5 @ 208-230V		Med-High, Med-Low, Low	5 or 7.5		
1/5	1.8 @ 208-230V		Med-Low, Low	5 or 7.5		
1/6	1.3 @ 208-230V		Low	5 or 7.5		
3/4	3.9 @ 208-230V	1075	All	10	Ball	FD6001
1/2	3.6 @ 208-230V		All	10		
1/3	3.0 @ 208-230V		All	5 or 7.5		
1/4	2.3 @ 208-230V		Med -Hi, Med-Low, Low	5 or 7.5		
1/5	2.0 @ 208-230V		Med- Low, Low	5 or 7.5		
1/2	7.0 @ 115V	1075	All	10	Sleeve	FDL6001
1/3	6.7 @ 115V		All	5 or 7.5		
1/4	4.4 @ 115V		Med-High, Med-Low, Low	5 or 7.5		
1/5	3.2 @ 115V		Med-Low, Low	5 or 7.5		
1/6	2.4 @ 115V		Low	5 or 7.5		
3/4	9.1 @ 115V	1075	All	10	Ball	FDL6002
1/2	6.8 @ 115V		All	10		
1/3	5.5 @ 115V		All	5 or 7.5		
1/4	3.0 @ 115V		Med-Hi, Med-Low, Low	5 or 7.5		
1/5	2.3 @ 115V		Med-Low, Low	5 or 7.5		