


NEW "MASTERFIT" MULTIPLE HORSEPOWER MOTORS FOR THE REPLACEMENT MARKET

Indoor Blower Motor

Catalog Model: FD6000
For use in different horsepower applications at
208-230 Volts, 60 Hz. Equivalent to 51-23022-41 .



Rating Max	Motor Rating Possibilities:		
	370V Capacitor	Speeds to Use	FLA
1/2 HP	10.0	All	3.9
1/3 HP	5.0-or-7.5	All	3.6
1/4 HP	5.0-or-7.5	Med-Hi MedLo, Lo	2.5
1/5 HP	5.0-or-7.5	MedLo, Lo	1.8
1/6 HP	5.0-or-7.5	Low	1.3

Motor Specs:	
RPM:	1075
Rot.:	Reversible
Amb.:	40 °C
Encl.:	Open
Shaft:	1/2"x 5.0" Flatted

Features:
Sleeve Bearings
Reversing Plug
Resilient Rings
Extended Thru Bolts
26" Leads
Mounting Holes in Shell
Automatic Protector
Conn. Dia. #130

Indoor Blower Motor

Catalog Model: FDL6001
For use in different horsepower applications at
115 Volts, 60 Hz. Equivalent to 51-23012-41 .



Rating Max	Motor Rating Possibilities:		
	370V Capacitor	Speeds to Use	FLA
1/2 HP	10.0	All	7.0
1/3 HP	5.0-or-7.5	All	6.7
1/4 HP	5.0-or-7.5	Med-Hi MedLo, Lo	4.4
1/5 HP	5.0-or-7.5	MedLo, Lo	3.2
1/6 HP	5.0-or-7.5	Low	2.4

Motor Specs:	
RPM:	1075
Rot.:	Reversible
Amb.:	40 °C
Encl.:	Open
Shaft:	1/2"x 5.0" Flatted

Features:
Sleeve Bearings
Reversing Plug
Resilient Rings
Extended Thru Bolts
26" Leads
Mounting Holes in Shell
Automatic Protector
Conn. Dia. #130

Condenser Fan Motor

Catalog Model: FSE6000
For use in different horsepower applications at
208-230 Volts, 60 Hz. Equivalent to 51-23053-21 .



Rating Max	Motor Rating Possibilities:		
	370V Capacitor	Speeds to Use	FLA
1/3 HP	7.5	Hi	2.8
1/5 HP	7.5	Lo	1.7

Motor Specs:	
RPM:	1075
Rot.:	Reversible
Amb.:	60 °C
Encl.:	Enclosed
Shaft:	1/2"x 6.0" Dbl Flat

Features:
Sleeve Bearings
Reversing Plug
Extended Thru Bolts
27" Leads
Automatic Protector
Mounting Holes in Shell
Conn. Dia. #16