

Carrier/BDP (continued)



HP	RPM	Speeds	Volts	Amps	Stock No.	Alt.	Rot.	Capacitor	Shaft Diameter & Length	Motor Dia.	"A" Dim.	Conn. Dia. No.	Cross Reference	Notes
1/2	1100	1	230	4.3	655		CCWLE	5MFD-370V	1/2" x 4-1/4"	5-5/8"	7-1/4"		HC44SL230	1
1/2	1050	1	460	0.9	FEH1056S		REV	10MFD/370V	1/2" x 3-5/16"	5-5/8"	5-5/16"	65	D802 3320	8
1/2	1050	1	200-230/460	4.6/2.3	OCA1056		REV	7.5MFD/440V	1/2" x 1-9/16"	5-5/8"	6-5/16"	66		1,5
1/2	1075	1	575	1.8	5OCA1056		CCWLE	7.5MFD/440V	1/2" x 1-9/16"	5-5/8"	5-9/16"	58		1,5
1/2	1075	1	230/460	4.7/2.3	759	OCA1056	CCWLE	7.5MFD-440V	1/2" x 2"	5-5/8"	6-1/4"	88u	HC43VL200,230, 1,10 460, HC44VL852	1,10
1/2	1050	1	460	1.0	755	FEH1056S	REV	10MFD-370V	1/2" x 3-3/8"	5-5/8"	5-1/4"	82u	HC44VL463A	1,10
1/2	1140	1	575	1.0	5OCA3056		REV	Three Phase	1/2" x 2-1/2"	5-5/8"	7"	95	P48J6A2 HD44ML461	1
3/4	1725	1	208-230/460	2.5-1.25	OCA3074		REV	Three Phase	1/2" x 2-1/2"	5-5/8"	9"	28	HD54KF652 HD46GA800	9
3/4	1140	1	208-230	3.8	OCA3076		REV	Three Phase	1/2" x 3"	5-5/8"	8-3/4"	95	HD46GK230	8
3/4	1140	1	460	1.9	OCA3076H		REV	Three Phase	1/2" x 3"	5-5/8"	8-3/4"	95	HD46GK460	8
1	1000	3	208-230	5.6	OCA1106		CWLE	25MFD/370V	5/8" x 3"	5-5/8"	7-5/8"	115	F48SX6V10 F48SX6V12 HC52AL230A HC52AL231A	1,7
SPL	1140	1	208-230/5.5/2.3-3.4 460/575		H978		REV	3 Phase	5/8" x 3-1/2"	6-1/2"	15"		HD52AK652 MAG. 176055	
5.0	1725	1	208-230/460	15.0/7.4	H979		REV	3 Phase	7/8" x 3-1/2"	6-1/2"	16"		HD60FK652 MAG. 182779	
3.0	1725	1	208-230/460	10.6/4.8	H980		REV	3 Phase	7/8" x 3-1/2"	6-1/2"	15"		HD60FK651 MAG. 176500	

- Notes:**
1. Ball Bearing
 2. Supplied with lead and plug assembly
 3. Includes 1/4-5/16" bushing
 4. Fits most 38GS Series
 5. Lug Mount
 6. Totally enclosed version of OCC1026
 7. Molex Terminal Plug
 8. Totally enclosed
 9. Rigid Base
 10. Item to be discontinued when stock is depleted

