

**EXACT REPLACEMENT PLASTIC IMPELLERS**



- Broan® & Nutone® Exact Replacement Impellers

SUPCO® Part No.	Replaces	Blade O.D.	Hole I.D.
SB001	Nutone® 68920	4 5/8"	.181
FB460	Broan® 9910379H	4 9/16"	.218

**PLASTIC BLOWER WHEELS**



Part No.	Shaft Rotation	Bottom Diameter	Depth	Top Diameter	Replaces
FB250	1/8" CW	2 1/2"	1"	2 11/16"	
FB590	1/4" CW	5 3/4"	2"	6 1/8"	Nutone® 59000A

**PLASTIC VENT HOOD FAN BLADES**



- Ducted & Non Ducted Vent Hoods

Part No.	Shaft	Diameter	No. Blades	Rotation	Pitch	Volume
FB660	7/32"	6 5/8"	5	CW	25°	High
FB665	7/32"	7/32"	5	CW	12°	Standard

Use with SM500 series or SM700 series that have 7/32" w/ flat shaft.  
Replaces Nutone 68929300 and many Broan blades.

**PLASTIC FAN BLADES - GENERAL PURPOSE**




- Celcon Plastic Construction
- Light Weight Design Reduces Bearing Wear & Vibrations
- 3 1/2" to 7" Diameter Sizes Available (1/2" increments)
- Integral Hub Available in 1/8", 3/16", 1/4" & 5/16" Sizes
- Color Coded Rotation White = CW Gray = CCW
- Eliminates Bent or Misaligned Blades
- Low Air Noise

Part No.	Shaft	Diameter	No. Blades	Rotation
FB350	3/16"	3 1/2"	4	CW
FB401	1/8"	4"	5	CW
FB402	3/16"	4"	5	CW
FB403	1/8"	4"	5	CCW
FB404	3/16"	4"	5	CCW
FB501	3/16"	5"	5	CW
FB504	3/16"	5"	5	CCW
FB550	3/16"	5"	4	CCW

Part No.	Shaft	Diameter	No. Blades	Rotation
FB601	3/16"	6"	6	CW
FB604	3/16"	6"	4	CCW
FB650	3/16"	6 1/2"	5	CW
FB651	1/4"	6 1/2"	5	CW
FB702	5/16"	7"	5	CW
FB703	1/4"	7"	5	CCW

**ALUMINUM FAN BLADES - GENERAL PURPOSE**



- 22 Gauge Aluminum Alloy Construction
- Light Weight Design Reduces Bearing Wear & Vibration
- Slotted Set Screw Hub Sizes 3/16", 7/32" & 1/4"

Part No.	Shaft	Diameter	No. Blades	Rotation	Pitch
FB152	3/16"	4"	10	CCW	35°
FB159	1/4"	4 1/2"	10	CCW	40°
FB180	1/4"	6"	4	CW	20°

**PLASTIC FAN BLADES - DIRECT REPLACEMENT & HUB TYPE**



- Available in Hub or Shaft Mount 1/8", 3/16"

Part No.	Shaft	Diameter	No. Blades	Rotation	Replaces
FB450	1/8"	4 1/2"	5	CCW	GE® WR60X114
FB455	3/16"	5 9/16"	5	CCW	Bohn® 5101B

**ALUMINUM CONDENSER FAN BLADES**



- Aluminum Construction
- 6" to 10" Diameter
- 5 Blades

Part No.	Diameter	No. Blades	Rotation	Pitch
FB101	6"	5	CW	30°
FB103	7"	5	CCW	20°
FB104	7"	5	CW	20°
FB105	8"	5	CCW	20°
FB106	8"	5	CW	20°
FB107	8 3/4"	5	CW	20°
FB108	10"	5	CCW	29°
FB109	10"	5	CW	22°

**LBK500 LINEBACKER® MOTOR PROTECTOR**



The LBK500 protects compressors and fans by ensuring "out-of-tolerance" capacitors are identified and notification is provided to confirm, and replace the capacitor.

- Extends the life of fan motor and compressor
- Prevents thermal damage
- Operates on 110 VAC and 208-240 VAC
- Use on 1 to 5 ton units

- Easy connections
- Connection wires included
- One year warranty
- UL® Recognized
- Operating Input Voltage 22 to 29 VAC

**TPMP2 THREE PHASE MOTOR PROTECTOR**



- Low Cost Three Phase Motor Protection
- Easy Installation
- Compact Design
- Monitors and Protects Against Phase Loss and Imbalance
- Operating Temperature -40°F to 167°F (-40°C to 75°C)
- 1/4" Male Spade Terminal Connections

Specifications	
Input Line Voltage	208 - 277 VAC
Control Voltage	18 - 240 VAC
Frequency	50/60 Hz
Imbalance	Fixed 7%
Total Power Consumption	3 VA Maximum
Contact Type	N.O. & N.C. Type C
Resistive	5 AMP 240 VAC/10 AMP 120 VAC
Fire Resistive Plastic	UL-94 VO
Dimensions	2.35" x 2.43" x 1.1" (59.7 x 61.7 x 27.9 mm)
Weight	2 oz. (54 gr)

**TPMPU UNIVERSAL 3-PHASE MOTOR PROTECTOR**



- Low Cost Universal Three Phase Motor Protection
- Easy Installation
- Minimizes Inventory
- Monitors and Protects Against Phase Loss, Reversal and Imbalance
- Response Time 80 Milliseconds Maximum
- Bright LED For On and Fault Indications

Specifications	
Input Line Voltage	180 - 600 VAC
Control Voltage	18 - 240 VAC
Frequency	50/60 Hz (cut wire for Hz)
Imbalance	Adjustable +4 to 20%
Total Power Consumption	3 VA Maximum
Contact Ratings	10 AMP SPDT
Resistive	10 AMP 240 VAC, 12 AMP 120 VAC/24 VAC
Inductive	4.5 AMP 230 VAC- Cos. 0.0.6