


UHS UNIVERSAL HUMIDIFIER SOLENOID VALVE REPLACEMENT KITS



- Each Kit Includes Solenoid Valve, Mounting Bracket and All Fittings to Remove and Replace the Existing Solenoid Valve
- Easy “Wrench-in” Installation
- Adjustable Water Flow Valve
- Time Saving
- Universal Replacement Reduces Inventory
- Economically Priced Compared to OEM Versions

| Part No. | Volts | Replaces |
|----------|-------|---|
| SUHS24 | 24 V | Aprilaire® 4040, General® 990-53, Honeywell® 320016939-002, Skuttle® A01-0814-148 |
| UHS120 | 120 V | Aprilaire® 4005, General® 990-52 |

NEOPRENE AIR TUBING



- Temperature Range: 0°F to 160°F (-17°C to 71°C)
- Pressure Range: -20 to 20 in. W.C.

| Part No. | Dimensions | Length |
|------------|------------|---------|
| SNAT3165 | 3/16" ID | 5 ft. |
| SNAT316100 | 3/16" ID | 100 ft. |
| SNAT185 | 1/8" ID | 5 ft. |

SILICONE AIR TUBING



- NSF 51, Soft, Red
- Temperature Range: -100°F to 500°F (-73°C to 260°C)
- 5 Foot Rolls

| Part No. | Dimensions | Working Pressure | Burst Pressure |
|----------|---------------------|------------------|----------------|
| SSRT185 | 1/8" ID x 5/16" OD | 25 psi | 75 psi |
| SSRT3165 | 3/16" ID x 5/16" OD | 20 psi | 60 psi |
| SSRT145 | 1/4" ID x 3/8" OD | 5 psi | 15 psi |

TR10 TEFLON O-RING KIT



- Package of 12 O-Rings
- 3 of Each Size

| OD Size | ID Size |
|---------|---------|
| 9/16" | 7/16" |
| 3/4" | 5/8" |
| 1" | 7/8" |
| 1 1/2" | 1 3/8" |

GB10 FINNY'S GASKET BOOK



- Replacements for Gaskets in Expansion and Solenoid Valves and Pumps
- 36 Different Gaskets Replace Most Common Gaskets Used Today
- Garlock Material Replaces All Older Materials