



Scan to see a full specifications, installation and agency certification information.

APPLICATIONS:

APPLIANCE | ELECTRICAL | HVAC/R | MARINE | POOL & SPA | RV



REPLACES

- **A-1:** EAC-501-ADJ
- **Diversified:** AC-503
- **Mars:** 32001, 32387, 32392
- **Robertshaw:** 3310-072
- **Supco:** TD72, TD73
- **Wagner/DiversiTech:** ADB-1

FEATURES

- ✓ Universal voltage operation
- ✓ Higher 1.5 amp power rating
- ✓ Compressor lockout/anti-short cycle timer
- ✓ Helps to protect compressors from damage caused by rapid short cycling

OVERVIEW

Upon application of power, the load is energized. When the thermostat or other switch opens or there is a loss of power, the load is de-energized and the delay period begins. The compressor will not start again during the delay period. Restart occurs after the delay period has elapsed.

SPECIFICATIONS

- **Voltage:** 18-240 VAC, 1.5 amps, 15 amp inrush
- **Frequency:** 50/60 Hz
- **Knob-adjustable delays:** .03-10 minimum (1.8-600 seconds)
- **Voltage drop:** 3.5 V typical, 4.5 V maximum @ 1.5 amps
- **Holding current minimum:** 40 mA

Content and specifications on sell sheets subject to change without notice.