

**M6KP-0092-CFA-072**

HFC, R-404A, 60Hz, 1-Phase, 115V

Availability: Standard US OEM

Mechanical		Electrical	
Unit Height (in):	13.1	Max Fuse Size:	30
Unit Length (in):	24.0	Min Circuit Ampacity:	20.2
Unit Width (in):	16.7	Compressor:	RST64C1E-CFA-102
Ship Weight (lbs):	.0	Compressor LRA - Low:	
Condenser Type:	Air	Compressor LRA - High:	77.0
CopeVap Water Storage:	NA	Compressor LRA - Half winding:	
Liquid Connection Size (in)/Type:	0.375 SWEAT	Compressor RLA	14.6
Suction Connection Size (in)/Type:	0.5 SWEAT	UL:	Listed
Discharge Line Size(in):	0.25	UL File #:	SA633
Water Inlet (in):		UL Guide Card:	LZFE
Water Outlet (in):			
Oil Type:	POE	Amps Per Motor:	
Oil Recharge Amount (oz):	15	Fan Motor Quantity:	1

**Performance**

Release Date:	24-May-2021	Return Gas Temp. (°F):	40
Compressor:	RST64C1E-CFA-102 x 1	Subcooling (°F):	5
Performance No:	20663	Air Flow Rate (CFM):	680

**90 °F Ambient Air Temperature**

Evap Temp(°F)	Unit Capacity (BTU/hr)	Cond. Temp.(°F)	Temp. Diff.(°F)	EER(BTU/wh)
-25	2,580	102.0	12.0	2.8
-20	3,030	103.4	13.4	3.1
-15	3,510	105.0	15.0	3.4

-10	4,010	106.7	16.7	3.7
-5	4,540	108.4	18.4	4.0
0	5,080	110.3	20.3	4.3
5	5,630	112.3	22.3	4.5
10	6,200	114.3	24.3	4.7
15	6,770	116.4	26.4	4.9
20	7,340	118.6	28.6	5.0
25	7,910	120.8	30.8	5.1