

M6KP-0092-CFA-072

HFC, R-407C, 60Hz, 1-Phase, 115V

Availability: Standard US OEM

Mechanical		Electrical	
Unit Height (in):	13.1	Max Fuse Size:	30
Unit Length (in):	24.0	Min Circuit Ampacity:	20.2
Unit Width (in):	16.7	Compressor:	RST64C1E-CFA-102
Ship Weight (lbs):	.0	Compressor LRA - Low:	
Condenser Type:	Air	Compressor LRA - High:	77.0
CopeVap Water Storage:	NA	Compressor LRA - Half winding:	
Liquid Connection Size (in)/Type:	0.375 SWEAT	Compressor RLA	14.6
Suction Connection Size (in)/Type:	0.5 SWEAT	UL:	Listed
Discharge Line Size(in):	0.25	UL File #:	SA633
Water Inlet (in):		UL Guide Card:	LZFE
Water Outlet (in):			
Oil Type:	POE	Amps Per Motor:	
Oil Recharge Amount (oz):	15	Fan Motor Quantity:	1

Performance

Release Date:	24-May-2021	Return Gas Temp. (°F):	40
Compressor:	RST64C1E-CFA-102 x 1	Subcooling (°F):	5
Performance No:	20664	Air Flow Rate (CFM):	680

90 °F Ambient Air Temperature

Evap Temp(°F)	Unit Capacity (BTU/hr)	Cond. Temp.(°F)	Temp. Diff.(°F)	EER(BTU/wh)
5	4,680	113.3	23.3	4.7
10	5,310	115.4	25.4	5.0
15	5,980	117.5	27.5	5.3

20	6,690	119.8	29.8	5.6
25	7,430	122.1	32.1	6.0