

M6ZL-0078-IAV-177

HFC, R-404A, 60Hz, 1-Phase, 208/230V

Availability: Standard US OEM

Mechanical**Electrical**

Unit Height (in):	11.8	Max Fuse Size:	15
Unit Length (in):	17.4	Min Circuit Ampacity:	8.6
Unit Width (in):	13.6	Compressor:	RFT26C1E-IAV-104
Ship Weight (lbs):	.0	Compressor LRA - Low:	
Condenser Type:	Air	Compressor LRA - High:	35.5
CopeVap Water Storage:	NA	Compressor LRA - Half winding:	
Liquid Connection Size (in)/Type:	0.375 SWEAT	Compressor RLA	6.4
Suction Connection Size (in)/Type:	0.5 SWEAT	UL:	Recognized
Discharge Line Size(in):	0.25	UL File #:	SA633
Water Inlet (in):		UL Guide Card:	LZFE2
Water Outlet (in):			
Oil Type:	POE	Amps Per Motor:	
Oil Recharge Amount (oz):	15	Fan Motor Quantity:	1

Performance

Release Date:	03-May-2017	Return Gas Temp. (°F):	40
Compressor:	RFT26C1E-IAV-104 x 1	Subcooling (°F):	5
Performance No:	11298	Air Flow Rate (CFM):	296

90 °F Ambient Air Temperature

Evap Temp(°F)	Unit Capacity (BTU/hr)	Cond. Temp.(°F)	Temp. Diff.(°F)	EER(BTU/wh)
-30	1,790	104.0	14.0	2.9
-25	2,090	105.5	15.5	3.1
-20	2,420	107.1	17.1	3.3

-15	2,770	108.9	18.9	3.6
-10	3,130	110.8	20.8	3.8
-5	3,500	112.8	22.8	4.0
0	3,870	115.0	25.0	4.1
5	4,250	117.2	27.2	4.2
10	4,610	119.6	29.6	4.3