

COLD CONTROLS

GC Series

Direct Replacement Cold Controls

PART NO.	REPLACES
GC116	GE® WR9X208
GC161	ELECTROLUX® 5303200810
GC175	GE® WR9X405
GC177	GE® WR9X411
GC185	WHIRLPOOL® 819470
GC188	GE® WR9X491
GC192	GE® WR9X499
GC193	ELECTROLUX® 5304404821
GC195	MAYTAG® 61005789

GC500 Series Kits

PART NO.	NORMAL °F		CALIBRATION °F		DIFF °F	CAPILLARY LENGTH
	OFF	ON	WARM OFF	COLD ON		
GC501	9	20	38	-16	11	42"
GC503	9	26	42.5	-16	17	42"
GC505	31	36	49	16	5	24"
GC506	18	31	48.5	-7	13	24"

Thermostats rated 125 VAC, 1/2 HP, 20 Amps F.L. - 80 Amps L.R., SPST switch action.

GC600 Series Kits

PART NO.	NORMAL °F		CALIBRATION °F		DIFF °F	CAPILLARY LENGTH
	OFF	ON	WARM OFF	COLD ON		
GC601	-5	4	22	-29	9	78"
GC602	-13	0	12	-30	13	78"
GC604	-12	6	20	-34	18	36"
GC607	-8	1	13	-23	9	31"
GC609	-7	9	23	-26	16	24"

Thermostats rated 125 VAC, 1/2 HP, 20 Amps F.L. - 80 Amps L.R., SPST switch action.

GC700 Series Kits

PART NO.	RANGE °F			CAPILLARY DETAILS		ELECTRICAL RATINGS 120/208/240 VAC		
	COLD OFF	WARM ON	DIFF °F	LENGTH	STYLE	SWITCH	F.I.A.L.	R.A.
GC701	52	93	6	18"	Air Coil	PST	20A	80A
GC707	52	93	6	36"	Straight	SPST	25A	80A

Thermostats rated 125 VAC, 1/2 HP, 20 Amps F.L. - 80 Amps L.R., SPST switch action.

THERMOSTATS

ML Series Defrost Thermostats

- Heavy Duty Rating 10 Amps @ 120 Volts / 5 Amps @ 240 Volts
- 12" Leads

THERMODISC®

PART NO.	OPEN °F	CLOSE °F	DIFF. °F	MARS®		MIN/MULTI
				UNILINE®		
ML37	37	47	10			
ML45	45	25	20	33008	31-001 17001	5 pc
ML50	50	30	20	33009	31-002 17003	5 pc
ML55	55	35	20	33010	31-003 17005	5 pc
ML60	60	40	20	33011	31-004 17007	5 pc
ML70	70	50	20	33012	31-005 17009	5 pc
ML80	80	30	50	33020	31-006 17011	5 pc



General Purpose L Series

"L" Series, Single Pole - Single Throw THERMODISC®

PART NO.	OPEN (°F)	CLOSE (°F)	DIFF (°F)
L120	120	110	10
L125	125	115	10
L130	130	115	15
L135	135	120	15
L140	140	120	20
L145	145	125	20
L150	150	130	20
L155	155	135	20
L160	160	140	20
L165	165	145	20
L170	170	150	20
L175	175	155	20
L180-20	180	160	20



"LD" Series - Single Pole - Double Throw

PART NO.	OPEN (°F)	CLOSE (°F)	DIFF (°F)
LD120	120	105	15
LD130	130	115	15
LD135	135	120	15
LD140	140	120	20
LD145	145	125	20
LD155	155	135	20
LD170	170	150	20
LD190	190	170	20
LD200	200	160	40
LD225	225	185	40
LD240	240	200	40
LD270	270	230	40
LD290	290	250	40

THERMODISC®

