## N96VSN

# Variable 25-Speed, Non-Communicating, Single-Stage Gas Furnace



#### Efficiency/Performance

- Up to 97.0% AFUE in upflow and horizontal positions, 95% AFUE in downflow position
- Variable-speed, constant torque ECM blower motor
- Supports single-stage and two-stage cooling units
- · Dehumidification feature in cooling
- All sizes can be installed in air quality management districts with a 40 ng/J NOx emissions requirement
- Cabinet air leakage less than 2.0% at 1.0 in. w.c. and cabinet air leakage less than 1.4% at 0.5 in. w.c. when tested in accordance with ASHRAE standard 193
- Control of continuous fan speed from a compatible thermostat

#### Reliability/Durability

- · Flame roll-out sensors standard
- Adjustable heating blower OFF delay
- · Factory set blower ON delay
- RPJ® primary heat exchanger
- Stainless steel secondary heat exchanger
- High temperature limit control designed to prevent overheating
- Direct ignition with Silicon Nitride ignitor
- Variable speed, constant torque ECM blower motor
- · Fully insulated steel cabinet

#### **Easy-to-Install and Service**

- On-board NFC antenna makes setup a tap away when using the service technician app
- Direct vent (2-pipe), single-pipe venting or ventilated combustion air
- 24 VAC humidifier terminal
- · Electronic air cleaner terminal
- · 35" (889mm) high, for ease of installation
- Quarter turn knobs for easy door removal and secure attachment
- Convertible to propane with gas conversion accessory kit
- Four position upflow/downflow/ horizontal (left/right) installation
- · Twelve different venting configurations
- Twinning capable with accessory (order separately)
- Through the casing flue pipe for counterflow or horizontal applications with accessory (order separately)
- Concentric vent available
- Slide out heat exchanger assembly and blower assembly

Illustrations and photographs are only representative. Some Product models may vary.







Use of the AHRI Certified TM Mark indicates a manufacturer's participation in the program. For verification of certification for individual products, go to www.ahridirectory.org.



CARBON MONOIDE POISONING AND FIRE HAZARD
Failure to follow this warning could result in personal injury, death and/or properly damage.
This furnace is not designed for use in recreation vehicles or outdoors.
Failure to follow this warning could result in personal injury, death and/or property damage.





### **Limited Warranty\***

- · Lifetime heat exchanger limited warranty with timely registration
- · Five-year parts limited warranty
- With timely registration, an additional five-year parts limited warranty
- \* For residential applications only. See warranty certificate for complete details and restrictions, including warranty coverage for other applications.