



R92MSN

Up to 92.1% AFUE,
Single-Stage, Gas Furnace

Efficiency/Performance

- Multi 18-speed, constant torque (MCT) ECM blower motor
- Enhanced diagnostics with easy to read 3 digit display for faults and status
- Up to 92.1% AFUE in upflow, horizontal and downflow positions
- Single-stage gas valve
- Cabinet air leakage less than 2.0% at 1.0 in. w.c. and cabinet air leakage less than 1.4% at 0.5 in. w.c. when tested in accordance with ASHRAE standard 193
- Approved for manufactured housing/mobile home applications with accessory (order separately)
- Select sizes approved for twinning, refer to accessory kit listing
- All sizes can be installed in air quality management districts with a 40 ng/J NOx emissions requirement

Reliability/Durability

- Flame roll-out sensors standard
- Adjustable heating blower OFF delay
- Factory set blower ON delay
- RPJ® primary heat exchanger
- Stainless steel secondary heat exchanger
- High temperature limit control designed to prevent overheating
- Direct ignition with Silicon Nitride ignitor
- High-quality, corrosion-resistant, one-piece steel cabinet

Easy-to-Install and Service

- Direct vent (2-pipe), single-pipe venting, or ventilated combustion air
- 24 VAC humidifier terminal, electronic air cleaner terminal
- 35" (889mm) high, for ease of installation
- Simplified, factory installed internal condensate drain system
- Quarter turn knobs for easy door removal and secure attachment
- Convertible to propane with gas conversion accessory kit
- Four position – upflow/downflow/horizontal (left/right) installation
- Twelve different venting configurations
- Through the casing flue pipe for counterflow or horizontal applications with accessory (order separately)
- Concentric vent available
- On-board NFC antenna makes setup a tap away when using the service technician app
- Slide out heat exchanger and blower assembly

Limited Warranty*

- 20-year heat exchanger limited warranty
- Five-year parts limited warranty
 - With timely registration, an additional five-year parts limited warranty


* For residential applications only. See warranty certificate for complete details and restrictions, including warranty coverage for other applications.

For California Residents: If installed with a manufactured (mobile) home conversion kit in SCAQMD: This furnace does not meet the SCAQMD Rule 1111 14 ng/J NOx emission limit, and thus is subject to a mitigation fee of up to \$450. This furnace is not eligible for the Clean Air Furnace Rebate Program: www.CleanAirFurnaceRebate.com

Illustrations and photographs are only representative. Some Product models may vary.



Use of the AHRI Certified TM Mark indicates a manufacturer's participation in the program. For verification of certification for individual products, go to www.ahridirectory.org.



ISO 9001
OM-514 Global



WARNING
CARBON MONOXIDE POISONING AND FIRE HAZARD
 Failure to follow this warning could result in personal injury, death, and/or property damage.
 This furnace is not designed for use in recreation vehicles or outdoors.
 Failure to follow this warning could result in personal injury, death, and/or property damage.

Unit Performance Data

Model Number	Heating Input (BTUH)	AFUE (up to)		Cooling Capacity CFM range @ 0.5 in. W.C. (125 Pa)	Operating Dimensions Height x Width x Depth inches (millimeters)	Shipping Weight lbs (kg)
		Upflow/H	Downflow			
R92MSN0401412A	40,000	92.1%	92.1%	195-1090	35 x 14-3/16 x 29-1/2 (889 x 361 x 750)	122 (55)
R92MSN0601714A	60,000	92.1%	92.1%	200-1340	35 x 17-1/2 x 29-1/2 (889 x 445 x 750)	136 (62)
R92MSN0801716A	80,000	92.1%	92.1%	270-1790	35 x 17-1/2 x 29-1/2 (889 x 445 x 750)	144 (65)
R92MSN1002120A	100,000	92.1%	92.1%	295-1870	35 x 21 x 29-1/2 (889 x 533 x 750)	160 (73)