

RFT18C1E-PFA

HFC, R-134a, 60 Hz, 1 - Phase, 115 V

Extended Medium Temp

Production Status: Available for sale to all U.S. customers. Please check with your local Copeland Representative for international availability.

Performance			Mechanical		
Evaporator Temp. (°F)	20.00	-10	Displacement (in <sup>3</sup> /Rev):	1.60	
Condensing Temp. (°F)	120.00	120	Displacement (ft <sup>3</sup> /Hr):		
Return Gas Temp. (°F)	40.00	40	Overall Length (in):	10.30	
Liquid Temp. (°F)	120.00	120	Overall Width (in):	7.10	
Capacity (BTU/hr)	4770	2060	Overall Height (in):	9.80	
Power (W):	861	557	Mounting Length (in):	8.00	
Current (Amps):	8.55	6.25	Mounting Width (in):	4.80	
EER(BTU/Wh):	5.55	3.7	Mounting Height (in):	10.40	
Mass Flow (lbs/hr):	83.5	35	Suction Size (in),Type:	1 / 2 Stub	
Sound Data @			Discharge Size (in),Type:	3 / 8 Stub	
Sound Power (dBA):	0 Avg	0 Max	Initial Oil Charge (oz):	22	
Vibration mils(peak-peak):	0.0 Avg	0.0 Max	Oil Recharge (oz):	20	
Record Date:	2011-07-18		Oil Type:	POE	
			Net Weight (lbs):	39.2	
			Internal Free Volume (in <sup>3</sup> ):		
			Horse Power:		
			*Overall compressor height on Copeland Brand Product's specified mounting grommets.		

Electrical		Capacitors				
		Type	Part No	Low MFD	High MFD	Volts User Description
LRA High* (Amps):	70.0	No data available in table				
LRA Low*(Amps):						
LRA Half Winding (Amps):						
MCC (Amps):	13.5					
Max Operating Current (Amps):						
RLA, MCC/1.4(use for contactor selection)(Amps):	9.6					
RLA, MCC/1.56(use for breaker & wire size selection)(Amps):	8.7					
RPM:	3500					
Box IP :						
UL File No:	SA-2337					
UL File Date:	1979-10-04					

\*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.

**Alternate Applications**

<b>Refrigerant</b>	<b>Voltage</b>	<b>Phase</b>	<b>Frequency</b>	<b>Application</b>
R-450A HFO	115	1	60	Extended Medium Temp
R-513A HFO	115	1	60	Extended Medium Temp