

Performance			Mechanical	
Evaporator Temp. (°F)	20.00	-10	Displacement (in <sup>3</sup> /Rev):	1.60
Condensing Temp. (°F)	120.00	120	Displacement (ft <sup>3</sup> /Hr):	
Return Gas Temp. (°F)	40.00	40	Overall Length (in):	10.30
Liquid Temp. (°F)	120.00	120	Overall Width (in):	7.10
Capacity (BTU/hr)	4070	1755	Overall Height (in):	9.80
Power (W):	757	490	Mounting Length (in):	8.00
Current (Amps):	8.2	6	Mounting Width (in):	4.80
EER(BTU/Wh):	5.4	3.6	Mounting Height (in):	10.40
Mass Flow (lbs/hr):	75.5	31.7	Suction Size (in),Type:	1 / 2 Stub
Sound Data @			Discharge Size (in),Type:	3 / 8 Stub
Sound Power (dBA):	0 Avg	0 Max	Initial Oil Charge (oz):	22
Vibration mils(peak-peak):	0.0 Avg	0.0 Max	Oil Recharge (oz):	20
Record Date:	2017-01-09		Oil Type:	POE
			Net Weight (lbs):	39.2
			Internal Free Volume (in <sup>3</sup> ):	
			Horse Power:	
			*Overall compressor height on Copeland Brand Product's specified mounting grommets.	

Electrical		Capacitors				
		Type	Part No	Low MFD	High MFD	Volts User Description
LRA High* (Amps):	70.0	No data available in table				
LRA Low*(Amps):						
LRA Half Winding (Amps):						
MCC (Amps):	13.5					
Max Operating Current (Amps):						
RLA, MCC/1.4(use for contactor selection)(Amps):	9.6					
RLA, MCC/1.56(use for breaker & wire size selection)(Amps):	8.7					
RPM:	3500					
Box IP :						
UL File No:						
UL File Date:						

\*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.

Alternate Applications

Refrigerant	Voltage	Phase	Frequency	Application
-------------	---------	-------	-----------	-------------

---

R-134a HFC	115	1	60	Extended Medium Temp
R-513A HFO	115	1	60	Extended Medium Temp

---