



SERIES RHP REGULATORS

SINGLE
STAGE

RHP SERIES SPECIAL PURPOSE

- Piston actuated seat for durability
- Easy-to-read single scale 2" gauges
- Steel case construction with polycarbonate lens
- Protective rubber gauge boots
- Porous metal inlet filter
- Fine mesh filter screen between inlet and seat
- T-handle for ease of pressure adjustment
- For all your testing and evaluating needs



RHP400

Stainless steel
pressure
adjusting screw

**MAXIMUM INLET
3000 PSIG**

- RHP200** Also can be used for operating pneumatic tools such as nail guns and impact wrenches
- RHP400 and RHP800** Purging and pressure testing regulators. Designed for the HVAC-R technician
- RHP800 and RHP1500** For high pressure testing applications
- RHP3000 and RHP3680** For high pressure testing of cylinders & vessels

PART# UPC#	RHP200* 13500	RHP218* 13501	RHP400 13000	RHP418 13001
CGA INLET	NITROGEN 580	AIR 346	NITROGEN 580	AIR 346
OUTLET CONNECTION	1/4" FLARE (M)	1/4" FLARE (M)	1/4" FLARE (M)	1/4" FLARE (M)
DEL. PSIG	5-180	5-180	20-400	20-400
REPLACEMENT 2" GAUGES	G4S; 200 PSI G7S; 4000 PSI	G4S; 200 PSI G7S; 4000 PSI	G8S; 600 PSI G7S; 4000 PSI	G8S; 600 PSI G7S; 4000 PSI

**RHP200; RHP400; RHP800
DIMENSIONS**

Depth:	4 1/4"
Width:	5 3/4"
Height:	5 1/4"
Weight:	2 1/2 lbs.

PART# UPC#	RHP800 13800	RHP818 13801
CGA INLET	NITROGEN 580	AIR 346
OUTLET CONNECTION	1/4" FLARE (M)	1/4" FLARE (M)
DEL. PSIG	50-800	50-800
REPLACEMENT 2" GAUGES	G34S; 1000 PSI G7S; 4000 PSI	G34S; 1000 PSI G7S; 4000 PSI

**RHP1500; RHP3000
DIMENSIONS**

Depth:	5 1/2"
Width:	6"
Height:	5 1/4"
Weight:	3 1/2 lbs.

**Adequate flow to operate most pneumatic equipment on the market today.*

PART# UPC#	RHP1500 13300	RHP1518 13301	RHP3000 13600	RHP3018 13601	RHP3680 13650
CGA INLET	NITROGEN 580	AIR 346	NITROGEN 580	AIR 346	NITROGEN 680
OUTLET CONNECTION	1/4" NPT (F)	1/4" NPT (F)	1/4" NPT (F)	1/4" NPT (F)	1/4" NPT (F)
DEL. PSIG	100-1500	100-1500	200-2500	200-2500	200-3000
REPLACEMENT 2" GAUGES	G3S; 3000 PSI G7S; 4000 PSI	G3S; 3000 PSI G7S; 4000 PSI	G7S; 4000 PSI G44S; 6000 PSI	G7S; 4000 PSI G44S; 6000 PSI	G7S; 4000 PSI G44S; 6000 PSI

For special needs such as 1/4" swage lock fittings, (panel mount, etc.), contact customer service for availability.

**RHP3680
MAXIMUM INLET
5000 PSIG**

NOTE: PSI/kPa, PSI/Kg, PSI/BAR Gauges available (Please Inquire)