

**RRT62C1E-IAA**

HFC, R-134a, 60 Hz, 1 - Phase, 115 V

**High Temp**

**Production Status:** Available for sale to all U.S. customers. Please check with your local Copeland Representative for international availability.

Performance			Mechanical		
Evaporator Temp. (°F)	45.00	20	Displacement (in <sup>3</sup> /Rev):	1.06	
Condensing Temp. (°F)	130.00	120	Displacement (ft <sup>3</sup> /Hr):		
Return Gas Temp. (°F)	65.00	65	Overall Length (in):	10.30	
Liquid Temp. (°F)	130.00	120	Overall Width (in):	7.10	
Capacity (BTU/hr)	5600	3440	Overall Height (in):	8.20	
Power (W):	848	623	Mounting Length (in):	8.00	
Current (Amps):	9.6	7.95	Mounting Width (in):	4.80	
EER(BTU/Wh):	6.6	5.5	Mounting Height (in):	8.80	
Mass Flow (lbs/hr):	97	54.5	Suction Size (in),Type:	3 / 8 Stub	
Sound Data @			Discharge Size (in),Type:	1 / 4 Stub	
Sound Power (dBA):	0 Avg	0 Max	Initial Oil Charge (oz):	15	
Vibration mils(peak-peak):	0.0 Avg	0.0 Max	Oil Recharge (oz):	13	
Record Date:	2008-06-19		Oil Type:	POE	
			Net Weight (lbs):	36.4	
			Internal Free Volume (in <sup>3</sup> ):		
			Horse Power:		
			*Overall compressor height on Copeland Brand Product's specified mounting grommets.		

Electrical		Capacitors				
LRA High* (Amps):	44.0	Type	Part No	Low MFD	High MFD	Volts User Description
LRA Low*(Amps):		No data available in table				
LRA Half Winding (Amps):						
MCC (Amps):	13.3					
Max Operating Current (Amps):						
RLA, MCC/1.4(use for contactor selection)(Amps):	9.5					
RLA, MCC/1.56(use for breaker & wire size selection)(Amps):	8.5					
RPM:	3500					
Box IP :						
UL File No:	SA-2337					
UL File Date:	2009-02-05					

\*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.

**Alternate Applications**

<b>Refrigerant</b>	<b>Voltage</b>	<b>Phase</b>	<b>Frequency</b>	<b>Application</b>
R-450A HFO	115	1	60	High Temp
R-513A HFO	115	1	60	High Temp