

RRT64C1E-IAV

HFC, R-134a, 60 Hz, 1 - Phase, 208/230 V

High Temp

Production Status: Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

Performance			Mechanical			
Evaporator Temp. (°F)	45.00	20	Displacement (in ³ /Rev):	1.25		
Condensing Temp. (°F)	130.00	120	Displacement (ft ³ /Hr):			
Return Gas Temp. (°F)	65.00	65	Overall Length (in):	10.30		
Liquid Temp. (°F)	130.00	120	Overall Width (in):	7.10		
Capacity (BTU/hr)	6610	4050	Overall Height (in):	8.70		
Power (W):	977	725	Mounting Length (in):	8.00		
Current (Amps):	5.6	4.7	Mounting Width (in):	4.80		
EER(BTU/Wh):	6.75	5.6	Mounting Height (in):	9.30		
Mass Flow (lbs/hr):	115	64.6	Suction Size (in),Type:	3 / 8 Stub		
Sound Data @			Discharge Size (in),Type:	1 / 4 Stub		
Sound Power (dBA):	0 Avg	0 Max	Initial Oil Charge (oz):	15		
Vibration mils(peak-peak):	0.0 Avg	0.0 Max	Oil Recharge (oz):	13		
Record Date:	2009-09-22		Oil Type:	POE		
			Net Weight (lbs):	37.5		
			Internal Free Volume (in ³):			
			Horse Power:			
			*Overall compressor height on Copeland Brand Product's specified mounting grommets.			

Electrical		Capacitors				
		Type	Part No	Low MFD	High MFD	Volt s User Description
LRA High* (Amps):	31.0					
LRA Low*(Amps):		Start Capacitor	014-0053-29	64.0	77.0	330
LRA Half Winding (Amps):						
MCC (Amps):	9					
Max Operating Current (Amps):						
RLA, MCC/1.4(use for contactor selection)(Amps):	6.4					
RLA, MCC/1.56(use for breaker & wire size selection)(Amps):	5.8					
RPM:						
Box IP :						
UL File No:	SA-2337					
UL File Date:	2009-02-05					

*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.

Alternate Applications

Refrigerant	Voltage	Phase	Frequency	Application
R-450A HFO	208/230	1	60	High Temp
R-513A HFO	208/230	1	60	High Temp