

RRT64C1E-IAA

HFO, R-450A, 60 Hz, 1 - Phase, 115 V

High Temp

Production Status: Preliminary data only - Contact your Copeland Representative.

Performance			Mechanical	
Evaporator Temp. (°F)	45.00	20	Displacement (in ³ /Rev):	1.25
Condensing Temp. (°F)	130.00	120	Displacement (ft ³ /Hr):	
Return Gas Temp. (°F)	65.00	65	Overall Length (in):	10.30
Liquid Temp. (°F)	130.00	120	Overall Width (in):	7.10
Capacity (BTU/hr)	6010	3770	Overall Height (in):	8.70
Power (W):	907	660	Mounting Length (in):	8.00
Current (Amps):	10.1	7.95	Mounting Width (in):	4.80
EER(BTU/Wh):	6.65	5.7	Mounting Height (in):	9.30
Mass Flow (lbs/hr):	110	63.3	Suction Size (in),Type:	3 / 8 Stub
Sound Data @			Discharge Size (in),Type:	1 / 4 Stub
Sound Power (dBA):	0 Avg	0 Max	Initial Oil Charge (oz):	15
Vibration mils(peak-peak):	0.0 Avg	0.0 Max	Oil Recharge (oz):	13
Record Date:	2017-01-12		Oil Type:	POE
			Net Weight (lbs):	37.5
			Internal Free Volume (in ³):	
			Horse Power:	
			*Overall compressor height on Copeland Brand Product's specified mounting grommets.	

Electrical		Capacitors				
LRA High* (Amps):	45.0	Type	Part No	Low MFD	High MFD	Volts User Description
LRA Low*(Amps):		No data available in table				
LRA Half Winding (Amps):						
MCC (Amps):	15.4					
Max Operating Current (Amps):						
RLA, MCC/1.4(use for contactor selection)(Amps):	11.0					
RLA, MCC/1.56(use for breaker & wire size selection)(Amps):	9.9					
RPM:	3500					
Box IP :						
UL File No:						
UL File Date:						
*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.						

Alternate Applications

Refrigerant	Voltage	Phase	Frequency	Application
-------------	---------	-------	-----------	-------------

R-134a HFC	115	1	60	High Temp
R-513A HFO	115	1	60	High Temp
