

RST40C1E-IAA

HFO, R-448A, 60 Hz, 1 - Phase, 115 V

Medium Temperature**Production Status:** Available for sale to all U.S. customers. Please check with your local Copeland Representative for international availability.

| Performance | | | Mechanical | | |
|----------------------------|------------|---------|---|------------|--|
| Evaporator Temp. (°F) | 20.00 | 0 | Displacement (in ³ /Rev): | .77 | |
| Condensing Temp. (°F) | 120.00 | 110 | Displacement (ft ³ /Hr): | | |
| Return Gas Temp. (°F) | 40.00 | 40 | Overall Length (in): | 10.30 | |
| Liquid Temp. (°F) | 120.00 | 110 | Overall Width (in): | 7.10 | |
| Capacity (BTU/hr) | 3330 | 2140 | Overall Height (in): | 8.70 | |
| Power (W): | 644 | 490 | Mounting Length (in): | 8.00 | |
| Current (Amps): | 7.9 | 6.8 | Mounting Width (in): | 4.80 | |
| EER(BTU/Wh): | 5.15 | 4.35 | Mounting Height (in): | 9.30 | |
| Mass Flow (lbs/hr): | 55.6 | 32.7 | Suction Size (in),Type: | 3 / 8 Stub | |
| Sound Data @ | | | Discharge Size (in),Type: | 1 / 4 Stub | |
| Sound Power (dBA): | 0 Avg | 0 Max | Initial Oil Charge (oz): | 15 | |
| Vibration mils(peak-peak): | 0.0 Avg | 0.0 Max | Oil Recharge (oz): | 13 | |
| Record Date: | 2016-02-08 | | Oil Type: | POE | |
| | | | Net Weight (lbs): | 36.8 | |
| | | | Internal Free Volume (in ³): | | |
| | | | Horse Power: | | |
| | | | *Overall compressor height on Copeland Brand Product's specified mounting grommets. | | |

| Electrical | | Capacitors | | | | |
|---|------|----------------------------|---------|---------|----------|------------------------|
| | | Type | Part No | Low MFD | High MFD | Volts User Description |
| LRA High* (Amps): | 50.0 | No data available in table | | | | |
| LRA Low*(Amps): | | | | | | |
| LRA Half Winding (Amps): | | | | | | |
| MCC (Amps): | 12.6 | | | | | |
| Max Operating Current (Amps): | | | | | | |
| RLA, MCC/1.4(use for contactor selection)(Amps): | 9.0 | | | | | |
| RLA, MCC/1.56(use for breaker & wire size selection)(Amps): | 8.1 | | | | | |
| RPM: | 3500 | | | | | |
| Box IP : | | | | | | |
| UL File No: | | | | | | |
| UL File Date: | | | | | | |

*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.

Alternate Applications

| Refrigerant | Voltage | Phase | Frequency | Application |
|-------------|---------|-------|-----------|----------------------|
| R-404A HFC | 115 | 1 | 60 | Extended Medium Temp |
| R-407C HFC | 115 | 1 | 60 | High Temp |
| R-449A HFO | 115 | 1 | 60 | Medium Temperature |