

RST40C1E-IAA

HFO, R-449A, 60 Hz, 1 - Phase, 115 V

Medium Temperature

Production Status: Available for sale to all U.S. customers. Please check with your local Copeland Representative for international availability.

Performance			Mechanical		
Evaporator Temp. (°F)	20.00	0	Displacement (in ³ /Rev):	.77	
Condensing Temp. (°F)	120.00	110	Displacement (ft ³ /Hr):		
Return Gas Temp. (°F)	40.00	40	Overall Length (in):	10.30	
Liquid Temp. (°F)	120.00	110	Overall Width (in):	7.10	
Capacity (BTU/hr)	3330	2140	Overall Height (in):	8.70	
Power (W):	644	490	Mounting Length (in):	8.00	
Current (Amps):	7.9	6.8	Mounting Width (in):	4.80	
EER(BTU/Wh):	5.15	4.35	Mounting Height (in):	9.30	
Mass Flow (lbs/hr):	55.6	32.7	Suction Size (in),Type:	3 / 8 Stub	
Sound Data @			Discharge Size (in),Type:	1 / 4 Stub	
Sound Power (dBA):	0 Avg	0 Max	Initial Oil Charge (oz):	15	
Vibration mils(peak-peak):	0.0 Avg	0.0 Max	Oil Recharge (oz):	13	
Record Date:	2016-02-08		Oil Type:	POE	
			Net Weight (lbs):	36.8	
			Internal Free Volume (in ³):		
			Horse Power:		
			*Overall compressor height on Copeland Brand Product's specified mounting grommets.		

Electrical		Capacitors				
LRA High* (Amps):	50.0	Type	Part No	Low MFD	High MFD	Volts User Description
LRA Low*(Amps):		No data available in table				
LRA Half Winding (Amps):						
MCC (Amps):	12.6					
Max Operating Current (Amps):						
RLA, MCC/1.4(use for contactor selection)(Amps):	9.0					
RLA, MCC/1.56(use for breaker & wire size selection)(Amps):	8.1					
RPM:	3500					
Box IP :						
UL File No:						
UL File Date:						

*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.

Alternate Applications

Refrigerant	Voltage	Phase	Frequency	Application
R-404A HFC	115	1	60	Extended Medium Temp
R-407C HFC	115	1	60	High Temp
R-448A HFO	115	1	60	Medium Temperature