

RST45C1E-IAA

HFC, R-404A, 60 Hz, 1 - Phase, 115 V

Extended Medium Temp

Production Status: Available for sale to all U.S. customers. Please check with your local Copeland Representative for international availability.

Performance			Mechanical		
Evaporator Temp. (°F)	20.00	-10	Displacement (in ³ /Rev):	.89	
Condensing Temp. (°F)	120.00	120	Displacement (ft ³ /Hr):		
Return Gas Temp. (°F)	40.00	40	Overall Length (in):	10.30	
Liquid Temp. (°F)	120.00	120	Overall Width (in):	7.10	
Capacity (BTU/hr)	4140	1845	Overall Height (in):	8.69	
Power (W):	890	617	Mounting Length (in):	8.00	
Current (Amps):	10.1	7.25	Mounting Width (in):	4.80	
EER(BTU/Wh):	4.6	3	Mounting Height (in):	9.31	
Mass Flow (lbs/hr):	98.5	41.8	Suction Size (in),Type:	3 / 8 Stub	
Sound Data @			Discharge Size (in),Type:	1 / 4 Stub	
Sound Power (dBA):	0 Avg	0 Max	Initial Oil Charge (oz):	15	
Vibration mils(peak-peak):	0.0 Avg	0.0 Max	Oil Recharge (oz):	13	
Record Date:	2007-08-06		Oil Type:	POE	
			Net Weight (lbs):	37.2	
			Internal Free Volume (in ³):		
			Horse Power:		
			*Overall compressor height on Copeland Brand Product's specified mounting grommets.		

Electrical		Capacitors				
		Type	Part No	Low MFD	High MFD	Volts User Description
LRA High* (Amps):	54.5	No data available in table				
LRA Low*(Amps):						
LRA Half Winding (Amps):						
MCC (Amps):	14.7					
Max Operating Current (Amps):						
RLA, MCC/1.4(use for contactor selection)(Amps):	10.5					
RLA, MCC/1.56(use for breaker & wire size selection)(Amps):	9.4					
RPM:	3500					
Box IP :						
UL File No:	SA-2337					
UL File Date:	1972-06-23					

*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.

Alternate Applications

Refrigerant	Voltage	Phase	Frequency	Application
R-407C HFC	115	1	60	High Temp
R-448A HFO	115	1	60	Medium Temperature
R-449A HFO	115	1	60	Medium Temperature