

**RST55C1E-CAV**

HFC, R-404A, 60 Hz, 1 - Phase, 208/230 V

**Extended Medium Temp**

**Production Status:** Available for sale to all U.S. customers. Please check with your local Copeland Representative for international availability.

Performance			Mechanical	
Evaporator Temp. (°F)	20.00	-10	Displacement (in <sup>3</sup> /Rev):	1.06
Condensing Temp. (°F)	120.00	120	Displacement (ft <sup>3</sup> /Hr):	
Return Gas Temp. (°F)	40.00	40	Overall Length (in):	10.30
Liquid Temp. (°F)	120.00	120	Overall Width (in):	7.10
Capacity (BTU/hr)	5310	2450	Overall Height (in):	8.70
Power (W):	1075	795	Mounting Length (in):	8.00
Current (Amps):	5.05	3.85	Mounting Width (in):	4.80
EER(BTU/Wh):	4.9	3.1	Mounting Height (in):	9.30
Mass Flow (lbs/hr):	126	55.3	Suction Size (in),Type:	3 / 8 Stub
Sound Data @			Discharge Size (in),Type:	1 / 4 Stub
Sound Power (dBA):	63 Avg	68 Max	Initial Oil Charge (oz):	15
Vibration mils(peak-peak):	0.0 Avg	0.0 Max	Oil Recharge (oz):	13
Record Date:	2017-05-18		Oil Type:	POE
			Net Weight (lbs):	38.0
			Internal Free Volume (in <sup>3</sup> ):	
			Horse Power:	
			*Overall compressor height on Copeland Brand Product's specified mounting grommets.	

Electrical		Capacitors				
LRA High* (Amps):	33.7	Type	Part No	Low MFD	High MFD	Volts User Description
LRA Low*(Amps):		No data available in table				
LRA Half Winding (Amps):						
MCC (Amps):	9.5					
Max Operating Current (Amps):						
RLA, MCC/1.4(use for contactor selection)(Amps):	6.8					
RLA, MCC/1.56(use for breaker & wire size selection)(Amps):	6.1					
RPM:	3500					
Box IP :						
UL File No:	SA-2337					
UL File Date:	1972-06-23					

\*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.

**Alternate Applications**

<b>Refrigerant</b>	<b>Voltage</b>	<b>Phase</b>	<b>Frequency</b>	<b>Application</b>
R-407C HFC	208/230	1	60	High Temp
R-448A HFO	208/230	1	60	Medium Temperature
R-448A HFO	208/230	1	60	Medium Temperature
R-449A HFO	208/230	1	60	Medium Temperature
R-449A HFO	208/230	1	60	Medium Temperature